

Package ‘RDBqc’

March 27, 2026

Title Quality check functions for RDBFIS

Version 0.1.3

Author Walter Zupa [aut, cre] <zupa@fondazionecoispa.org>,
Isabella Bitetto [aut, cre] <bitetto@fondazionecoispa.org>,
Alessandro Mannini [aut] <alessandro.mannini@irbim.cnr.it>,
Loredana Casciaro [cbt] <casciaro@coispa.eu>,
Sebastien Alfonso [cbt] <salfonso@coispa.eu>,
Vasiliki Sgardeli [aut] <vsgard@hcmr.gr>

Maintainer Walter Zupa [aut, cre] <zupa@fondazionecoispa.org>

Description The package contains functions used to perform a priori and a posteriori quality checks on RDBFIS data.

License GPL (>= 3)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Depends R (>= 4.1.0)

Imports dplyr, ggplot2, rworldmap, sp, rworldxtra, data.table, grDevices, magrittr, tidyverse, fish-methods, tidyr, gridExtra, scales, outliers, sf, methods, reshape2, cowplot, plyr, readr, ggpubr, stringr, tidyselect, lattice, HH

LazyData true

Suggests rmarkdown, knitr, markdown

VignetteBuilder knitr

Contents

aer_catch	4
ALK_tab_example	5
Catch_tab_example	5
catfau_check	6
check_age_MEDBS_AR	6
check_cs_header	7
check_EF_FDI_A	8
check_EF_FDI_G	8
check_EF_FDI_H	9
check_EF_FDI_I	10

check_EF_FDI_J	10
check_EF_taskII2	11
check_EF_taskIII	12
check_EF_taskVII2	12
check_EF_TaskVII31	13
check_EF_TaskVII32	14
check_gfcm_header	14
check_150_TaskVII.3.1	15
check_ldf_TaskVII.2	16
check_lengths_MEDBS_AR	16
check_lmat_TaskVII.3.2	17
check_lw_TaskVII.2	18
check_lw_TaskVII.3.2	19
check_maturity_MEDBS_AR	20
check_minmax150_TaskVII.3.1	21
check_minmax1_TaskVII.2	22
check_n_trips_MEDBS_AR	23
check_presence_taskII2	23
check_RD_FDI_A	24
check_RD_FDI_G	25
check_RD_FDI_H	25
check_RD_FDI_I	26
check_RD_FDI_J	27
check_RD_taskII2	27
check_RD_taskIII	28
check_RD_taskVII2	29
check_RD_taskVII31	29
check_RD_TaskVII32	30
check_species_catfau_TaskVII.3.2	31
Check_Tot_Disc	32
Check_Tot_Disc_gear	33
Check_Tot_Disc_gear_Q	34
Check_Tot_Disc_metier	35
Check_Tot_Land	36
Check_Tot_Land2	37
Check_Tot_Land3	38
Check_Tot_Land_gear	39
Check_Tot_Land_gear_Q	40
Check_Tot_Land_metier	41
check_weights_MEDBS_AR	42
circabc	43
combination_taskII2	43
data_ex	44
data_exampleCL	44
Discard_tab_example	45
FDI_AER_land_landvalue	45
fdi_a_catch	46
FDI_checks_spatial_HI	47
FDI_check_coord	48
FDI_coverage	48
FDI_cov_tableA	49
FDI_cov_tableG	50

FDI_cov_tableJ	51
FDI_cross_checks_AG	52
FDI_cross_checks_AH	53
FDI_cross_checks_IG	54
FDI_cross_checks_JG	54
FDI_disc_coverage	55
FDI_fishdays_cov	56
fdi_g_effort	56
fdi_h_spatial_land	57
fdi_h_spatial_landings	57
fdi_i_spatial_effort	58
fdi_j_capacity	58
FDI_landweight_cov	59
FDI_prices_cov	59
FDI_prices_not_null	60
FDI_vessel_lenth	61
FDI_vessel_numbers	62
GFCM_check_headers	62
GFCM_cov_II2	63
GFCM_cov_task_iii	64
GP_tab_example	64
GSAlist	65
Landing_tab_example	65
MA_tab_example	66
MEDBSSP	66
MEDBS_ALK	67
MEDBS_ALK_MLAA	67
MEDBS_ALK_NB	68
MEDBS_Catch_CAA	69
MEDBS_Catch_coverage	70
MEDBS_Catch_LW	70
MEDBS_check_disaggregated	71
MEDBS_check_duplicates	72
MEDBS_check_missing_years	73
MEDBS_comp_disc_YQ	74
MEDBS_comp_disc_YQ_fishery	75
MEDBS_comp_land_Q_VL	75
MEDBS_comp_land_Q_VL_fishery	76
MEDBS_comp_land_YQ	77
MEDBS_comp_land_YQ_fishery	78
MEDBS_discard_coverage	78
MEDBS_disc_mean_weight	79
MEDBS_GP_check	80
MEDBS_ks	81
MEDBS_Landing_coverage	82
MEDBS_land_mean_weight	82
MEDBS_lengthclass_0	83
MEDBS_length_ind	84
MEDBS_LFD	85
MEDBS_LW_check	86
MEDBS_MA_check	87
MEDBS_ML_check	87

MEDBS_plot_discard_ts	88
MEDBS_plot_disc_vol	89
MEDBS_plot_landing_ts	90
MEDBS_plot_land_vol	91
MEDBS_SA_check	91
MEDBS_SL_check	92
MEDBS_SOP	93
MEDBS_weight_0	94
MEDBS_weight_minus1	95
MEDBS_yr_missing_length	96
minmaxLtaskVII2	97
minmaxLtaskVII31	97
ML_tab_example	98
RCG_check_AL	98
RCG_check_CL	99
RCG_check_LFD	100
RCG_check_LFD_comm_cat	101
RCG_check_loc	101
RCG_check_lw	102
RCG_check_mat	103
RCG_check_mat_ogive	104
RCG_summarize_ind_meas	105
RCG_summarize_trips	105
read.coded.file	106
SA_tab_example	107
sex_mat	107
SL_tab_example	108
SSPP	108
task_ii2	109
task_iii	109
task_vii2	110
task_vii31	110
task_vii32	111

Index **112**

aer_catch	<i>AER catch table</i>
-----------	------------------------

Description

AER catch table

Usage

aer_catch

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 104 rows and 18 columns.

Author(s)

Vasiliki Sgardeli <vsgard@hcmr.gr>

ALK_tab_example *ALK table in MED&BS datacall format*

Description

ALK table in MED&BS datacall format

Usage

ALK_tab_example

Format

An object of class data.frame with 62 rows and 114 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

Catch_tab_example *Catch table in MED&BS datacall format*

Description

Catch table in MED&BS datacall format

Usage

Catch_tab_example

Format

An object of class data.frame with 57 rows and 171 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

catfau_check	<i>catfau_check in GFCM datacall format</i>
--------------	---

Description

catfau_check in GFCM datacall format

Usage

catfau_check

Format

An object of class `data.frame` with 355 rows and 5 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

check_age_MEDBS_AR	<i>Cross check of number of age measurements between MED&BS ALK table and AR Table 2.2</i>
--------------------	--

Description

The function compares the number of age measurements reported in MED & BS data call ALK table with the information reported in the table 2.2 ("Biol variables") of the Annual Report. The user have to define the two source tables as data frames in the ALK and AR parameters. The analysis should be constrained at the selected country level (MS), geographical sub-area GSA and year.

Usage

```
check_age_MEDBS_AR(
  ALK,
  AR,
  MS,
  GSA,
  SP,
  year,
  species_list = RDBqc::SSPP,
  OUT = FALSE,
  verbose = TRUE
)
```

Arguments

ALK	data frame containing MED&BS ALK table
AR	data frame containing Annual Report data table 2.2
MS	member state code
GSA	Geographical Subarea
SP	Species 3-alpha code
year	Reference year for the analysis
species_list	table of species 3-alpha codes, reporting the MED & BS mandatory species
OUT	Default is FALSE. If set as TRUE tables in csv will be saved in the OUTPUT folder created in the working directory
verbose	boolean. If TRUE a message is printed.

Value

A list of three data frames is returned. The first list element contains all the species matching between the two tables; the second list element reports the species reported in Annual Report but not in the MED&BS ALK table; the third list element contains the species reported in MED&BS ALK table but not in the Annual Report table 2.2. Warnings are reported for data of species not included in the MED&BS data call, and for species expected in the Work Plan and not reported in the Annual Report. Errors are reported for species expected in both tables but not present at least in one of the two tables.

Author(s)

Walter Zupa zupa@fondazionecoispa.org

check_cs_header	<i>Headers check for CS table</i>
-----------------	-----------------------------------

Description

Headers check for CS table

Usage

```
check_cs_header(cs, verbose = FALSE)
```

Arguments

cs	RCG sampling table (CS)
verbose	boolean. If TRUE messages are returned

Value

The data frame of CS data is returned with the expected format used by the QC functions

Examples

```
check_cs_header(data_ex)
```

check_EF_FDI_A	<i>Check empty fields in FDI A table</i>
----------------	--

Description

The function checks the presence of not allowed empty data in the given table.

Usage

```
check_EF_FDI_A(data, verbose = TRUE)
```

Arguments

data	FDI Task A table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list returns the number of NA for each reference column. The second list provides the index of each NA in the reference column.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_EF_FDI_A(fdi_a_catch)
```

check_EF_FDI_G	<i>Check empty fields in FDI G table</i>
----------------	--

Description

The function checks the presence of not allowed empty data in the given table.

Usage

```
check_EF_FDI_G(data, verbose = TRUE)
```

Arguments

data	FDI Task G table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list returns the number of NA for each reference column. The second list provides the index of each NA in the reference column.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_EF_FDI_G(fdi_g_effort)
```

check_EF_FDI_H	<i>Check empty fields in FDI H table</i>
----------------	--

Description

The function checks the presence of not allowed empty data in the given table.

Usage

```
check_EF_FDI_H(data, verbose = TRUE)
```

Arguments

data	FDI Task H table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_EF_FDI_H(fdi_h_spatial_landings)
```

check_EF_FDI_I	<i>Check empty fields in FDI I table</i>
----------------	--

Description

The function checks the presence of not allowed empty data in the given table.

Usage

```
check_EF_FDI_I(data, verbose = TRUE)
```

Arguments

data	FDI Task I table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_EF_FDI_I(fdi_i_spatial_effort)
```

check_EF_FDI_J	<i>Check empty fields in FDI J table</i>
----------------	--

Description

The function checks the presence of not allowed empty data in the given table.

Usage

```
check_EF_FDI_J(data, verbose = TRUE)
```

Arguments

data	FDI Task J table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_EF_FDI_J(fdi_j_capacity)
```

check_EF_taskII2

Check empty fields in GFCM Task II.2 table

Description

The function checks the presence of not allowed empty data in the given table, according to the [GFCM, 2018. GFCM Data Collection Reference Framework \(DCRF\). Version: 20.1](#)

Usage

```
check_EF_taskII2(data, verbose = TRUE)
```

Arguments

data GFCM Task II.2 table

verbose boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_EF_taskII2(task_ii2)
```

check_EF_taskIII *Check empty fields in GFCM Task III table*

Description

The function checks the presence of not allowed empty data in the given table, according to the [GFCM, 2018. GFCM Data Collection Reference Framework \(DCRF\). Version: 20.1](#)

Usage

```
check_EF_taskIII(data, verbose = TRUE)
```

Arguments

data GFCM Task III table
 verbose boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Author(s)

Loredana Casciaro casciaro@coispa.eu
 Sebastien Alfonso salfonso@coispa.eu
 Walter Zupa zupa@coispa.it

Examples

```
check_EF_taskIII(task_iii)
```

check_EF_taskVII2 *Check empty fields in GFCM Task VII.2 table*

Description

The function checks the presence of not allowed empty data in the given table, according to the [GFCM, 2018. GFCM Data Collection Reference Framework \(DCRF\). Version: 20.1](#)

Usage

```
check_EF_taskVII2(data, verbose = TRUE)
```

Arguments

data GFCM Task VII.2 table
 verbose boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_EF_taskVII2(task_vii2)
```

check_EF_TaskVII31	<i>Check empty fields in GFCM Task VII.3.1 table</i>
--------------------	--

Description

The function checks the presence of not allowed empty data in the given table, according to the [GFCM, 2018. GFCM Data Collection Reference Framework \(DCRF\). Version: 20.1](#)

Usage

```
check_EF_TaskVII31(data, verbose = TRUE)
```

Arguments

data	GFCM Task VII.3.1 table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_EF_TaskVII31(task_vii31)
```

check_EF_TaskVII32 *Check empty fields in GFCM Task VII.3.2 table*

Description

The function checks the presence of not allowed empty data in the given table, according to the [GFCM, 2018. GFCM Data Collection Reference Framework \(DCRF\). Version: 20.1](#)

Usage

```
check_EF_TaskVII32(data, verbose = TRUE)
```

Arguments

data	GFCM Task VII.3.2 table
verbose	boolean. If TRUE a message is printed.

Value

Two lists are returned by the function. The first list gives the number of NA for each reference column. The second list gives the index of each NA in the reference column.

Author(s)

Loredana Casciaro casciaro@coispa.eu
 Sebastien Alfonso salfonso@coispa.eu
 Walter Zupa zupa@coispa.it

Examples

```
check_EF_TaskVII32(task_vii32)
```

check_gfcm_header *Headers check for GFCM tables*

Description

Headers check for GFCM tables

Usage

```
check_gfcm_header(data, task, verbose = FALSE)
```

Arguments

data	GFCM table data frame
task	character value reporting the specific GFCM table (task) of the data. Allowed values: "II.2", "III", "VII.2", "VII.3.1", "VII.3.2"
verbose	boolean. If TRUE messages are returned

Value

The data frame of the selected GFCM task is returned with the expected format used by the QC functions

Examples

```
check_gfcm_header(task_ii2, "TASK_II.2", verbose = FALSE)
```

check_150_TaskVII.3.1 *Consistency of L50 values in Task VII.3.1 table*

Description

Function to verify the consistency of L50 reported in the TaskVII.3.1 table by mean of plot by GSA, species and sex

Usage

```
check_150_TaskVII.3.1(data, MS, GSA, SP = NA, verbose = FALSE)
```

Arguments

data	GFCM Task VII.3.1 table
MS	member state code
GSA	GSA code
SP	species reference code in the three alpha code format
verbose	boolean. If TRUE a message is printed.

Value

The function returns a plot to visualize the L50 time series by species and sex for the selected MS and GSA

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_150_TaskVII.3.1(task_vii31, MS = "ITA", GSA = "19", SP = "HKE")
```

check_ldf_TaskVII.2 *Consistency of length frequency distributions*

Description

Function to verify the consistency of the length frequency distributions (LFD) reported in the TaskVII.2 table. The functions generates plots of the LFD by species, source, segment and year.

Usage

```
check_ldf_TaskVII.2(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	GFCM Task II.2 table
MS	member state code
GSA	GSA code
SP	species reference code in the three alpha code format
verbose	boolean. If TRUE a message is printed.

Value

The function returns a table with the comparison between min/max lengths observed for each species with theoretical values.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_ldf_TaskVII.2(task_vii2, MS = "ITA", GSA = "18", SP = "HKE")
```

check_lengths_MEDBS_AR

Cross check of number of lengths between MED&BS catch table and AR Table 2.1

Description

The function compares the number of length measurements reported in MED & BS data call catch table with the information reported in the table 2.1 ("Stocks") of the Annual Report. The user have to define the two source tables as data frames in the MEDBS and AR parameters. The analysis should be constrained at the selected country level (MS) and at the selected year.

Usage

```

check_lengths_MEDBS_AR(
  MEDBS,
  AR,
  MS,
  GSA,
  SP,
  year,
  species_list = RDBqc::SSPP,
  OUT = FALSE,
  verbose = FALSE
)

```

Arguments

MEDBS	data frame containing MED&BS catch table
AR	data frame containing Annual Report data
MS	member state code
GSA	Geographical Subarea
SP	Species 3-alpha code
year	Reference year for the analysis
species_list	table of species 3-alpha codes, reporting the MED & BS mandatory species
OUT	Default is FALSE. If set as TRUE tables in csv will be saved in the OUTPUT folder created in the working directory
verbose	boolean. If TRUE a message is printed.

Value

The function returns a data frame reporting the total number of length measurements related to catches, landings and discards conducted in the selected country and year. MED & BS data will be reported as sum of the measurements by year and sum of the trips reported by quarter in the year.

Author(s)

Walter Zupa zupa@fondazionecoispa.org

check_lmat_TaskVII.3.2

Plot of the maturity stages per length for each sex and species

Description

Function to plot the lengths at maturity stages by species and sex to easily identify outliers.

Usage

```

check_lmat_TaskVII.3.2(data, MS, GSA, SP, verbose = TRUE)

```

Arguments

data	GFCM Task VII.3.2 table
MS	member state code
GSA	GSA code
SP	species reference code in the three alpha code format
verbose	boolean. If TRUE a message is printed.

Value

The function return a plot of the maturity stages per length and sex per species.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_lmat_TaskVII.3.2(task_vii32, MS = "ITA", GSA = "18", SP = "CTC")
```

check_lw_TaskVII.2 *Plot of the length-weight relationship*

Description

Function to check the consistency of length-weight relationship in the GFCM Task VII.2 table for the selected species.

Usage

```
check_lw_TaskVII.2(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	GFCM Task VII.2 table
MS	country code
GSA	GSA code
SP	species reference code in the three alpha code format
verbose	boolean value to obtain further explanation messages from the function

Value

The function return a plot of the length weight relationship for the selected species.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_lw_TaskVII.2(task_vii2, MS = "ITA", GSA = "18", SP = "BOG")
```

check_lw_TaskVII.3.2 *Plot of the length-weight relationship by sex*

Description

Function to check the consistency of length-weight relationship in the GFCM Task VII.3.2 table by sex for the selected species.

Usage

```
check_lw_TaskVII.3.2(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	GFCM Task VII.3.2 table
MS	country code
GSA	GSA code
SP	species reference code in the three alpha code format
verbose	boolean value to obtain further explanation messages from the function

Value

The function return a plot of the length-weight relationship by sex for the selected species.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_lw_TaskVII.3.2(task_vii32, MS = "ITA", GSA = "18", SP = "CTC")
```

check_maturity_MEDBS_AR

Cross check of number of maturity measurements between MED&BS ML table and AR Table 2.2

Description

The function compares the number of maturity measurements reported in MED & BS data call ML table with the information reported in the table 2.2 ("Biol variables") of the Annual Report. The user have to define the two source tables as data frames in the ML and AR parameters. The analysis should be constrained at the selected country level (MS), geographical sub-area GSA and year. When GSA and SP parameter are NA, the analysis is conducted on all the GSAs and species included in the data frame for the selected country.

Usage

```
check_maturity_MEDBS_AR(
  ML,
  AR,
  MS,
  GSA,
  SP,
  year,
  species_list = RDBqc::SSPP,
  OUT = FALSE,
  verbose = TRUE
)
```

Arguments

ML	data frame containing MED&BS ML table
AR	data frame containing Annual Report data table 2.2
MS	member state code
GSA	Geographical Subarea
SP	Species 3-alpha code
year	Reference year for the analysis
species_list	table of species 3-alpha codes, reporting the MED & BS mandatory species
OUT	Default is FALSE. If set as TRUE tables in csv will be saved in the OUTPUT folder created in the working directory
verbose	boolean. If TRUE a message is printed.

Value

A list of three data frames is returned. The first list element contains all the species matching between the two tables; the second list element reports the species reported in Annual Report but not in the MED&BS ML table; the third list element contains the species reported in MED&BS ML table but not in the Annual Report table 2.2. Warnings are reported for data of species not included in the MED&BS data call, and for species expected in the Work Plan and not reported in the Annual Report. Errors are reported for species expected in both tables but not present at least in one of the two tables.

Author(s)

Walter Zupa zupa@fondazionecoispa.org

check_minmax150_TaskVII.3.1

Comparison between min/max L50 observed for each species and sex with theoretical values

Description

Function to verify the consistency of L50 reported in the TaskVII.3.1 table with the theoretical values reported in the minmaxLtaskVII31 table. The function allows to identify the records in which the observed L50 are greater or lower than the expected ones.

Usage

```
check_minmax150_TaskVII.3.1(data, tab_L50, MS, GSA)
```

Arguments

data	GFCM Task VII.3.1 table
tab_L50	Theoretical values of min/max L50 for each species and sex
MS	member state code
GSA	GSA code

Value

The function returns a table with the comparison between min/max L50 observed for each species and sex with theoretical values.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_minmax150_TaskVII.3.1(task_vii31, minmaxLtaskVII31, MS = "ITA", GSA = "19")
```

check_minmax1_TaskVII.2

Comparison between min/max observed for each species with theoretical values

Description

Function to verify the consistency of the lengths reported in the TaskVII.2 table with the theoretical values reported in the minmaxLtaskVII2 table. The function allows to identify the records in which the observed lengths are greater or lower than the expected ones.

Usage

```
check_minmax1_TaskVII.2(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	GFCM Task II.2 table
MS	member state code
GSA	GSA code
SP	species reference code in the three alpha code format
verbose	boolean. If TRUE a message is printed.

Value

The function returns a table with the comparison between min/max lengths observed for each species with theoretical values.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_minmax1_TaskVII.2(task_vii2, minmaxLtaskVII2, MS = "ITA", GSA = "18")
```

 check_n_trips_MEDBS_AR

Cross check of number of trips between MED&BS catch table and AR Table 2.5

Description

The function compares the number of trips reported in MED & BS data call catch table with the information reported in the table 2.5 ("Sampling plan biol") of the Annual Report. The user have to define the two source tables as data frames in the MEDBS and AR parameters. The analysis should be constrained at the selected country level (MS) and at the selected year.

Usage

```
check_n_trips_MEDBS_AR(MEDBS, AR, MS, year, OUT = FALSE, verbose = FALSE)
```

Arguments

MEDBS	data frame containing MED&BS catch table
AR	data frame containing Annual Report data
MS	member state code
year	Reference year for the analysis
OUT	Default is FALSE. If set as TRUE tables in csv will be saved in the OUTPUT folder created in the working directory
verbose	boolean. If TRUE a message is printed.

Value

The function returns a data frame reporting the total number of trips related to catches, landings and discards conducted in the selected country and year. MED & BS data will be reported both as sum of the trips by year and as sum of the trips reported by quarter in the year.

Author(s)

Walter Zupa zupa@fondazionecoispa.org

check_presence_taskII2

Check of missing combination GSA/Fleet segment per year

Description

Function to verify the completeness of the GSA/Fleet segments in Task II.2 table, as reported in the combination_taskII2 table.

Usage

```
check_presence_taskII2(data1, data2, MS, GSA)
```

Arguments

data1	GFCM Task II.2 table
data2	List of combination of the expected GSA/Fleet segments per year for Task II.2 table
MS	member state code
GSA	GSA code

Value

The function returns a list of missing combinations GSA/Fleet segment per year.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_presence_taskII2(task_ii2, combination_taskII2, MS = "ITA", GSA = "18")
```

check_RD_FDI_A	<i>Check duplicated records in FDI A table</i>
----------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 19 columns generates duplicate records.

Usage

```
check_RD_FDI_A(data, verbose = TRUE)
```

Arguments

data	FDI Task A table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 19 columns of the FDI A table.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_RD_FDI_A(fdi_a_catch)
```

check_RD_FDI_G	<i>Check duplicated records in FDI G table</i>
----------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 15 columns generates duplicate records.

Usage

```
check_RD_FDI_G(data, verbose = TRUE)
```

Arguments

data	FDI Task G table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 15 columns of the FDI G table.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_RD_FDI_G(fdi_g_effort)
```

check_RD_FDI_H	<i>Check duplicated records in FDI H table</i>
----------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 15 columns generates duplicate records.

Usage

```
check_RD_FDI_H(data, verbose = TRUE)
```

Arguments

data	FDI Task H table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 20 columns of the FDI G table.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_RD_FDI_H(fdi_h_spatial_landings)
```

check_RD_FDI_I

Check duplicated records in FDI I table

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 15 columns generates duplicate records.

Usage

```
check_RD_FDI_I(data, verbose = TRUE)
```

Arguments

data FDI Task I table

verbose boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 19 columns of the FDI G table.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_RD_FDI_I(fdi_i_spatial_effort)
```

check_RD_FDI_J	<i>Check duplicated records in FDI J table</i>
----------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 15 columns generates duplicate records.

Usage

```
check_RD_FDI_J(data, verbose = TRUE)
```

Arguments

data	FDI Task J table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 7 columns of the FDI G table.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_RD_FDI_J(fdi_j_capacity)
```

check_RD_taskII2	<i>Check duplicated records in GFCM Task II.2 table</i>
------------------	---

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 5 columns generates duplicate records.

Usage

```
check_RD_taskII2(data, verbose = TRUE)
```

Arguments

data	GFCM Task II.2 table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 5 columns of the Task II.2 table.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_RD_taskII2(task_ii2)
```

check_RD_taskIII	<i>Check duplicated records in GFCM Task III table</i>
------------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 10 columns generates duplicate records.

Usage

```
check_RD_taskIII(data, verbose = TRUE)
```

Arguments

data GFCM Task III table

verbose boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 10 columns of the Task Task III table.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_RD_taskIII(task_iii)
```

check_RD_taskVII2	<i>Check duplicated records in GFCM Task VII.2 table</i>
-------------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 9 columns generates duplicate records.

Usage

```
check_RD_taskVII2(data, verbose = TRUE)
```

Arguments

data	GFCM Task VII.2 table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 9 columns of the Task Task VII.2 table.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_RD_taskVII2(task_vii2)
```

check_RD_taskVII31	<i>Check duplicated records in GFCM Task VII.3.1 table</i>
--------------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 5 columns generates duplicate records.

Usage

```
check_RD_taskVII31(data, verbose = TRUE)
```

Arguments

data	GFCM Task VII.3.1 table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 5 columns of the Task Task VII.3.1 table.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_RD_taskVII31(task_vii31)
```

check_RD_TaskVII32	<i>Check duplicated records in GFCM Task VII.3.2 table</i>
--------------------	--

Description

The function check the presence of duplicated records. In particular, it checks whether the combination of the first 10 columns generates duplicate records.

Usage

```
check_RD_TaskVII32(data, verbose = TRUE)
```

Arguments

data	GFCM Task VII.3.2 table
verbose	boolean. If TRUE a message is printed.

Value

The function returns the indices of the duplicated rows, checking the unique combinations of the first 10 columns of the Task Task VII.3.2 table.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_RD_TaskVII32(task_vii32)
```

 check_species_catfau_TaskVII.3.2

Check mismatching species/Catfau and Sex per maturity stages for Task VII.3.2 table

Description

Function to check the correct codification of faunistic category according to species and sex in Task VII.3.2 table.

Usage

```
check_species_catfau_TaskVII.3.2(
  data,
  species,
  matsex,
  MS,
  GSA,
  SP,
  verbose = FALSE
)
```

Arguments

data	GFCM Task VII.3.2 table
species	List of combination of species/faunistic category for Task VII.3.2 table
matsex	List of combination of sex/maturity stages for Task VII.3.2 table
MS	member state code
GSA	GSA code
SP	species code
verbose	boolean. If TRUE messages are returned

Value

Two vectors are returned by the function. The first provides the list of mismatching combination of species/faunistic categories. The second vector provides the list of mismatching combination of sex/maturity stages. Furthermore, a plot of the length distribution by sex and maturity is returned for the selected species.

Author(s)

Loredana Casciaro casciaro@coispa.eu

Sebastien Alfonso salfonso@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
check_species_catfau_TaskVII.3.2(task_vii32, catfau_check, sex_mat,
  MS = "ITA", GSA = "18", SP = "HKE"
)
```

Check_Tot_Disc	<i>Comparing total discards in weight between MEDBS and FDI EU Data Calls</i>
----------------	---

Description

The function compares the discards in weight values reported in the MEDBS discards by length table with the one reported in the FDI Table A catch table. The analysis is done at MS, GSA and species level

Usage

```
Check_Tot_Disc(data, data1, MS, GSA, SP, MEDBSSP, verbose = FALSE, OUT = FALSE)
```

Arguments

data	data frame containing MEDBS discards by length table
data1	data frame containing FDI Table A Catch data
MS	member state 3 alpha code
GSA	FAO Geographical Sub Area code (GSA9, GSA29, etc)
SP	ASFIS FAO 3alpha code of the choosen species
MEDBSSP	look up table in which requested MEDBS Data Call species (see MEDBS data call Annex I) are listed
verbose	boolean. If TRUE a message is printed
OUT	Default is FALSE. If set as TRUE plots and tables in csv will be saved in the OUTPUT folder created in the working directory

Value

The function returns a plot comparison by year of the discards in weight provided through the MEDBS and FDI Data Calls. Moreover a csv file with the actual values will be created. Plot, csv and rds output files will be saved in the dedicated folders in OUTPUT folder

Author(s)

Alessandro Mannini alessandro.mannini@irbim.cnr.it

Examples

```
# Check_Tot_Disc(MEDBS,FDI,"ITA","GSA10","HKE",MEDBSSP)
# The function works by one country, subarea and species each.
# It is not possible assign more country, subarea or species.
```

Check_Tot_Disc_gear *Comparing total discards in weight between MEDBS and FDI EU Data Calls by Country, GSA, Species and Gear*

Description

The function compares the discards in weight values reported in the MEDBS discards by length table with the one reported in the FDI Table A catch table. The analysis is done at MS, GSA, species and gear level

Usage

```
Check_Tot_Disc_gear(
  data,
  data1,
  MS,
  GSA,
  SP,
  MEDBSSP,
  verbose = TRUE,
  OUT = FALSE
)
```

Arguments

data	data frame containing MEDBS discards by length table
data1	data frame containing FDI Table A Catch data
MS	member state 3 alpha code
GSA	FAO Geographical Sub Area code (GSA9, GSA29, etc)
SP	ASFIS FAO 3alpha code of the choosen species
MEDBSSP	look up table in which requested MEDBS Data Call species (see MEDBS data call Annex I) are listed
verbose	boolean. If TRUE a message is printed
OUT	Default is FALSE. If set as TRUE plots and tables in csv will be saved in the OUTPUT folder created in the working directory

Value

The function returns plots comparison by year of the discards in weight provided through the MEDBS and FDI Data Calls. Moreover a csv file with the actual values will be created. Plot, csv and rds output files will be saved in the dedicated folders in OUTPUT folder

Author(s)

Alessandro Mannini alessandro.mannini@irbim.cnr.it

Examples

```
# Check_Tot_Disc_gear(MEDBS,FDI,"ITA","GSA10","HKE",MEDBSSP)
# The function works by one country, subarea and species each.
# It is not possible assign more country, subarea or species.
```

Check_Tot_Disc_gear_Q *Comparing total discards in weight between MEDBS and FDI EU Data Calls by Country, GSA, Species and Gear*

Description

The function compares the discards in weight values reported in the MEDBS discards by length table with the one reported in the FDI Table A catch table. The analysis is done at MS, GSA, species and gear level

Usage

```
Check_Tot_Disc_gear_Q(
  data,
  data1,
  MS,
  GSA,
  SP,
  MEDBSSP,
  verbose = TRUE,
  OUT = FALSE
)
```

Arguments

data	data frame containing MEDBS discards by length table
data1	data frame containing FDI Table A Catch data
MS	member state 3 alpha code
GSA	FAO Geographical Sub Area code (GSA9, GSA29, etc)
SP	ASFIS FAO 3alpha code of the choosen species
MEDBSSP	look up table in which requested MEDBS Data Call species (see MEDBS data call Annex I) are listed
verbose	boolean. If TRUE a message is printed
OUT	Default is FALSE. If set as TRUE plots and tables in csv will be saved in the OUTPUT folder created in the working directory

Value

The function returns plots comparison by year of the discards in weight provided through the MEDBS and FDI Data Calls. Moreover a csv file with the actual values will be created. Plot, csv and rds output files will be saved in the dedicated folders in OUTPUT folder

Author(s)

Alessandro Mannini alessandro.mannini@irbim.cnr.it

Examples

```
# Check_Tot_Disc_gear_Q (MEDBS,FDI,"ITA","GSA10","HKE",MEDBSSP,verbose=TRUE,OUT=FALSE)
# The function works by one country, subarea and species each.
# It is not possible assign more country, subarea or species.
```

Check_Tot_Disc_metier *Comparing total discards in weight between MEDBS and FDI EU Data Calls by Country, GSA, Species and Metier*

Description

The function compares the discards in weight values reported in the MEDBS discards by length table with the one reported in the FDI Table A catch table. The analysis is done at MS, GSA, species and metier level

Usage

```
Check_Tot_Disc_metier(
  data,
  data1,
  MS,
  GSA,
  SP,
  MEDBSSP,
  verbose = TRUE,
  OUT = FALSE
)
```

Arguments

data	data frame containing MEDBS discards by length table
data1	data frame containing FDI Table A Catch data
MS	member state 3 alpha code
GSA	FAO Geographical Sub Area code (GSA9, GSA29, etc)
SP	ASFIS FAO 3alpha code of the choosen species
MEDBSSP	look up table in which requested MEDBS Data Call species (see MEDBS data call Annex I) are listed
verbose	boolean. If TRUE a message is printed
OUT	Default is FALSE. If set as TRUE plots and tables in csv will be saved in the OUTPUT folder created in the working directory

Value

The function returns plots comparison by year of the discards in weight provided through the MEDBS and FDI Data Calls. Moreover a csv file with the actual values will be created. Plot, csv and rds output files will be saved in the dedicated folders in OUTPUT folder

Author(s)

Alessandro Mannini alessandro.mannini@irbim.cnr.it

Examples

```
# Check_Tot_Disc_metier(MEDBS,FDI,"ITA","GSA10","HKE",MEDBSSP,verbose=TRUE,OUT=FALSE)
# The function works by one country, subarea and species each.
# It is not possible assign more country, subarea or species.
```

Check_Tot_Land	<i>Comparing total landings in weight between MEDBS and FDI EU Data Calls</i>
----------------	---

Description

The function compares the landings in weight values reported in the MEDBS landings by length table with the one reported in the FDI Table A catch table. The analysis is done at MS, GSA and species level

Usage

```
Check_Tot_Land(data, data1, MS, GSA, SP, MEDBSSP, verbose = FALSE, OUT = FALSE)
```

Arguments

data	data frame containing MEDBS landings by length table
data1	data frame containing FDI Table A Catch data
MS	member state 3 alpha code
GSA	FAO Geographical Sub Area code (GSA9, GSA29, etc)
SP	ASFIS FAO 3alpha code of the choosen species
MEDBSSP	look up table in which requested MEDBS Data Call species (see MEDBS data call Annex I) are listed
verbose	boolean. If TRUE a message is printed
OUT	Default is FALSE. If set as TRUE plots and tables in csv will be saved in the OUTPUT folder created in the working directory

Value

The function returns a plot comparison by year of the landings in weight provided through the MEDBS and FDI Data Calls. Moreover a csv file with the actual values will be created. Plot, csv and rds output files will be saved in the dedicated folders in OUTPUT folder

Author(s)

Alessandro Mannini alessandro.mannini@irbim.cnr.it

Examples

```
# Check_Tot_Land(MEDBS,FDI,"ITA","GSA10","HKE",MEDBSSP,verbose=TRUE,OUT=FALSE)

# The function works by one country, subarea and species each.
# It is not possible assign more country, subare or species.
```

Check_Tot_Land2	<i>Comparing total landings in weight between MEDBS, FDI and AER EU Data Calls</i>
-----------------	--

Description

The function compares the landings in weight values reported in the MEDBS landings by length table with the ones reported in the FDI Table A catch table and AER data (<https://stecf.jrc.ec.europa.eu/reports/economic>). The analysis is done at MS, GSA and species level

Usage

```
Check_Tot_Land2(
  data,
  data1,
  data2,
  MS,
  GSA,
  SP,
  MEDBSSP,
  verbose = TRUE,
  OUT = FALSE
)
```

Arguments

data	data frame containing MEDBS landings by length table
data1	data frame containing FDI Table A Catch data
data2	data frame containing AER landings data
MS	member state 3 alpha code
GSA	FAO Geographical Sub Area code (GSA9, GSA29, etc)
SP	ASFIS FAO 3alpha code of the choosen species
MEDBSSP	look up table in which requested MEDBS Data Call species (see MEDBS data call Annex I) are listed
verbose	boolean. If TRUE a message is printed
OUT	Default is FALSE. If set as TRUE plots and tables in csv will be saved in the OUTPUT folder created in the working directory

Value

The function returns a plot comparison by year of the landings in weight provided through the MEDBS, FDI and AER Data Calls. Moreover a csv file with the actual values will be created. Plot, csv and rds output files will be saved in the dedicated folders in OUTPUT folder

Author(s)

Alessandro Mannini alessandro.mannini@irbim.cnr.it

Examples

```
# Check_Tot_Land2(MEDBS,FDI,AER,"ITA","GSA10","HKE",MEDBSSP,verbose=TRUE,OUT=FALSE)

# The function works by one country, subarea and species each.
# It is not possible assign more country, subarea or species.
```

Check_Tot_Land3	<i>Comparing total landings in weight between MEDBS, FDI and AER EU Data Calls</i>
-----------------	--

Description

The function compares the landings in weight values reported in the MEDBS landings by length table with the ones reported in the FDI Table A catch table and AER input data (map_fsfao.xlsx) . The analysis is done at MS, GSA and species level

Usage

```
Check_Tot_Land3(
  data,
  data1,
  data2,
  MS,
  GSA,
  SP,
  MEDBSSP,
  verbose = TRUE,
  OUT = FALSE
)
```

Arguments

data	data frame containing MEDBS landings by length table
data1	data frame containing FDI Table A Catch data
data2	data frame containing AER landings data
MS	member state 3 alpha code
GSA	FAO Geographical Sub Area code (GSA9, GSA29, etc)
SP	ASFIS FAO 3alpha code of the choosen species
MEDBSSP	look up table in which requested MEDBS Data Call species (see MEDBS data call Annex I) are listed
verbose	boolean. If TRUE a message is printed
OUT	Default is FALSE. If set as TRUE plots and tables in csv will be saved in the OUTPUT folder created in the working directory

Value

The function returns a plot comparison by year of the landings in weight provided through the MEDBS,FDI and AER Data Calls. Moreover a csv file with the actual values will be created. Plot, csv and rds output files will be saved in the dedicated folders in OUTPUT folder

Author(s)

Alessandro Mannini alessandro.mannini@irbim.cnr.it

Examples

```
# Check_Tot_Land3(MEDBS, FDI, AER, "ITA", "GSA10", "HKE", MEDBSSP, verbose = TRUE, OUT = FALSE)

# The function works by one country, subarea and species each.
# It is not possible assign more country, subare or species.
```

Check_Tot_Land_gear *Comparing total landings in weight between MEDBS and FDI EU Data Calls by Country, GSA, Species and Gear*

Description

The function compares the landings in weight values reported in the MEDBS landings by length table with the one reported in the FDI Table A catch table. The analysis is done at MS, GSA, species and gear level

Usage

```
Check_Tot_Land_gear(
  data,
  data1,
  MS,
  GSA,
  SP,
  MEDBSSP,
  verbose = TRUE,
  OUT = FALSE
)
```

Arguments

data	data frame containing MEDBS landings by length table
data1	data frame containing FDI Table A Catch data
MS	member state 3 alpha code
GSA	FAO Geographical Sub Area code (GSA9, GSA29, etc)
SP	ASFIS FAO 3alpha code of the choosen species
MEDBSSP	look up table in which requested MEDBS Data Call species (see MEDBS data call Annex I) are listed
verbose	boolean. If TRUE a message is printed
OUT	Default is FALSE. If set as TRUE plots and tables in csv will be saved in the OUTPUT folder created in the working directory

Value

The function returns plots comparison by year of the landings in weight provided through the MEDBS and FDI Data Calls. Moreover a csv file with the actual values will be created. Plot, csv and rds output files will be saved in the dedicated folders in OUTPUT folder

Author(s)

Alessandro Mannini alessandro.mannini@irbim.cnr.it

Examples

```
# Check_Tot_Land_gear(MEDBS,FDI,"ITA","GSA10","HKE",MEDBSSP)

# The function works by one country, subarea and species each.
# It is not possible assign more country, subarea or species.
```

Check_Tot_Land_gear_Q *Comparing total landings in weight between MEDBS and FDI EU Data Calls by Country, GSA, Species and Gear*

Description

The function compares the landings in weight values reported in the MEDBS landings by length table with the one reported in the FDI Table A catch table. The analysis is done at MS, GSA, species and gear level

Usage

```
Check_Tot_Land_gear_Q(
  data,
  data1,
  MS,
  GSA,
  SP,
  MEDBSSP,
  verbose = TRUE,
  OUT = FALSE
)
```

Arguments

data	data frame containing MEDBS landings by length table
data1	data frame containing FDI Table A Catch data
MS	member state 3 alpha code
GSA	FAO Geographical Sub Area code (GSA9, GSA29, etc)
SP	ASFIS FAO 3alpha code of the choosen species
MEDBSSP	look up table in which requested MEDBS Data Call species (see MEDBS data call Annex I) are listed
verbose	boolean. If TRUE a message is printed
OUT	Default is FALSE. If set as TRUE plots and tables in csv will be saved in the OUTPUT folder created in the working directory

Value

The function returns plots comparison by year of the landings in weight provided through the MEDBS and FDI Data Calls. Moreover a csv file with the actual values will be created. Plot, csv and rds output files will be saved in the dedicated folders in OUTPUT folder

Author(s)

Alessandro Mannini alessandro.mannini@irbim.cnr.it

Examples

```
# Check_Tot_Land_gear_Q (MEDBS,FDI,"ITA","GSA10","HKE",MEDBSSP)

# The function works by one country, subarea and species each.
# It is not possible assign more country, subarea or species.
```

Check_Tot_Land_metier *Comparing total landings in weight between MEDBS and FDI EU Data Calls by Country, GSA, Species and Metier*

Description

The function compares the landings in weight values reported in the MEDBS landings by length table with the one reported in the FDI Table A catch table. The analysis is done at MS, GSA, species and metier level

Usage

```
Check_Tot_Land_metier(
  data,
  data1,
  MS,
  GSA,
  SP,
  MEDBSSP,
  verbose = TRUE,
  OUT = FALSE
)
```

Arguments

data	data frame containing MEDBS landings by length table
data1	data frame containing FDI Table A Catch data
MS	member state 3 alpha code
GSA	FAO Geographical Sub Area code (GSA9, GSA29, etc)
SP	ASFIS FAO 3alpha code of the choosen species
MEDBSSP	look up table in which requested MEDBS Data Call species (see MEDBS data call Annex I) are listed
verbose	boolean. If TRUE a message is printed
OUT	Default is FALSE. If set as TRUE plots and tables in csv will be saved in the OUTPUT folder created in the working directory

Value

The function returns plots comparison by year of the landings in weight provided through the MEDBS and FDI Data Calls. Moreover a csv file with the actual values will be created. Plot, csv and rds output files will be saved in the dedicated folders in OUTPUT folder

Author(s)

Alessandro Mannini alessandro.mannini@irbim.cnr.it

Examples

```
# Check_Tot_Land_metier(MEDBS, FDI, "ITA", "GSA10", "HKE", MEDBSSP, verbose = TRUE, OUT = FALSE)

# The function works by one country, subarea and species each.
# It is not possible assign more country, subarea or species.
```

check_weights_MEDBS_AR

Cross check of number of weight measurements between MED&BS GP table and AR Table 2.2

Description

The function compares the number of weight measurements reported in GP table of MED & BS data call with the information reported in the table 2.2 ("Biol variables") of the Annual Report. The user have to define the two source tables as data frames in the GP and AR parameters. The analysis should be constrained at the selected country level (MS), geographical sub-area GSA and year.

Usage

```
check_weights_MEDBS_AR(
  GP,
  AR,
  MS,
  GSA,
  SP,
  year,
  species_list = RDBqc::SSPP,
  OUT = FALSE,
  verbose = TRUE
)
```

Arguments

GP	data frame containing MED&BS GP table
AR	data frame containing Annual Report data table 2.2
MS	member state code
GSA	Geographical Subarea
SP	Species 3-alpha code
year	Reference year for the analysis
species_list	table of species 3-alpha codes, reporting the MED & BS mandatory species
OUT	Default is FALSE. If set as TRUE tables in csv will be saved in the OUTPUT folder created in the working directory
verbose	boolean. If TRUE a message is printed.

Value

A list of three data frames is returned. The first list element contains all the species matching between the two tables; the second list element reports the species reported in Annual Report but not in the MED&BS GP table; the third list element contains the species reported in MED&BS GP table but not in the Annual Report table 2.2. Warnings are reported for data of species not included in the MED&BS data call, and for species expected in the Work Plan and not reported in the Annual Report. Errors are reported for species expected in both tables but not present at least in one of the two tables.

Author(s)

Walter Zupa zupa@fondazionecoispa.org

circabc

Ports coordinates according to codification CIRCABC

Description

Ports coordinates according to codification CIRCABC

Usage

circabc

Format

An object of class `data.frame` with 24335 rows and 5 columns.

Author(s)

CIRCABC

combination_taskII2

combination_taskII2 in GFCM datacall format

Description

combination_taskII2 in GFCM datacall format

Usage

combination_taskII2

Format

An object of class `data.frame` with 60 rows and 4 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

data_ex	<i>RCG CS example</i>
---------	-----------------------

Description

RCG CS example

Usage

data_ex

Format

An object of class `data.frame` with 9099 rows and 40 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

data_exampleCL	<i>RCG CL example</i>
----------------	-----------------------

Description

RCG CL example

Usage

data_exampleCL

Format

An object of class `data.frame` with 35 rows and 11 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

Discard_tab_example *Discard table in MED&BS datacall format*

Description

Discard table in MED&BS datacall format

Usage

Discard_tab_example

Format

An object of class data.frame with 21 rows and 114 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

FDI_AER_land_landvalue

Cross check of landings or landings' value between the FDI and AER databases

Description

The function compares landings (var='landings') or landings' value (var='value') by SP and YEAR between the FDI and AER databases for the given MS. By default, the comparison is done by GSA, GEAR and METIER. Optionally, the user can select a higher level of aggregation (e.g. 'MS', 'GSA', etc.) (see level variable)

Usage

```
FDI_AER_land_landvalue(  
  FDI,  
  AER,  
  var = "landings",  
  MS,  
  level = "GSA",  
  YEAR = NA,  
  GSA = NA,  
  SP = NA,  
  OUT = FALSE,  
  verbose = FALSE  
)
```

Arguments

FDI	(mandatory) data frame containing FDI catch data (i.e. TABLE_A_CATCH)
AER	(mandatory) data frame containing AER catch data (i.e. map_fsfao)
var	(mandatory) string to select the variable of interest. Use either 'landings' for landings or 'value' for landings' value.
MS	(mandatory) The MS code (e.g. 'GRC'). Only one MS code is allowed.
level	(optional) character to select the level of aggregation of variable 'var', i.e. 'MS', 'GSA', 'GEAR' or 'METIER'. E.g. if level 'GEAR' is selected, the comparison will be performed by 'MS', 'GSA' and 'GEAR'. Default level is 'METIER'.
YEAR	(optional) vector of years to perform the check on. Default is NA, which will produce a check for all the years found in both data frames
GSA	(optional) vector string of GSAs for the given MS to produce the check on (e.g. GSA = c('GSA20', 'GSA22')). Default is NA, which will produce the check for all GSAs existing in the data frames.
SP	(optional) vector string of species FAO 3-alpha codes to produce the checks on (e.g. SPECIES = c('DPS', 'TGS')). Default is NA, which will produce the check for all SP existing in the data frames.
OUT	If set as TRUE a table in csv will be saved in the OUTPUT folder created in the working directory. Default is FALSE
verbose	(optional) boolean, if TRUE messages are printed. Default is FALSE.

Value

The function returns a data frame containing all entries found in FDI, in AER and in both dataframes, with the last column reporting the ratio FDI/AER for the selected var. This ratio equals 1 if the two entries are the same, differs from 1 if the two entries differ or is NA if the entry is missing in one of the two dataframes. This output table is also saved in .csv files if OUT is TRUE.

Author(s)

Vasiliki Sgardeli vsgard@hcmr.gr

Examples

```
FDI_AER_land_landvalue(FDI=fdi_a_catch, AER=aer_catch, var='landings',
  level='GEAR', MS='PSP', YEAR=NA, GSA=c('GSA97', 'GSA98'), SP=NA, OUT = TRUE, verbose = TRUE)
```

fdi_a_catch

fdi_a_catch in FDI DGMAREMED&BS datacall format

Description

fdi_a_catch in FDI DGMAREMED&BS datacall format

Usage

```
fdi_a_catch
```

Format

An object of class `data.frame` with 2600 rows and 23 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

FDI_checks_spatial_HI *check NA values in spatial columns of both table H and I*

Description

The function checks the incorrect combination of NA in the spatial columns in both table H (Landings by rectangle) and table I (Effort by rectangle). The following check are included:

1. presence of NA values in 'c_square' field when 'rectangle_type', 'rectangle_lat', 'rectangle_lon' are all NA;
2. the presence any data in 'rectangle_type', 'rectangle_lat', 'rectangle_lon' when 'c_square' is reported;
3. the presence of any data in 'c-squares' when 'rectangle_type', 'rectangle_lat', 'rectangle_lon' are filled in.

Furthermore the function identifies the records without any sub-region assignment.

Usage

```
FDI_checks_spatial_HI(data, MS, verbose = FALSE)
```

Arguments

<code>data</code>	data frame of one between FDI table H (Landings by rectangle) and table I (Effort by rectangle)
<code>MS</code>	Country code
<code>verbose</code>	boolean. If TRUE a message is printed.

Value

The function returns a list of 2 tables. The first (`NA_inconsistencies`) reports the records with the inconsistencies detected in spatial of the selected table, while the second one reports the record without any `sub_region` assignment.

Author(s)

Walter Zupa zupa@coispa.it

Examples

```
FDI_checks_spatial_HI(data = fdi_h_spatial_landings, MS = "PSP", verbose = TRUE)
FDI_checks_spatial_HI(data = fdi_i_spatial_effort, MS = "PSP", verbose = TRUE)
```

FDI_check_coord	<i>Compatibility of the geographical coordinates with rectangle type</i>
-----------------	--

Description

The function checks the compatibility of the geographical coordinates (latitude and longitude) with the value provided for the rectangle type.

Usage

```
FDI_check_coord(data, MS, verbose = FALSE)
```

Arguments

data	data frame of one FDI table between H (Landings by rectangle) and table I (Effort by rectangle)
MS	Country code
verbose	boolean. If TRUE a message is printed.

Value

The input data frame is filtered and is returned retaining the only records in which at least one among latitude and longitude is not compatible with the rectangle type. Two more columns ('lat.check' and 'lon.check') are added to the data frame structure to report the results of the checks respectively for latitude and longitude.

Author(s)

Walter Zupa zupa@coispa.it

Examples

```
FDI_check_coord(data = fdi_i_spatial_effort, MS = "PSP", verbose = TRUE)
```

FDI_coverage	<i>Coverage of data by GSA and year (reporting the number of records)</i>
--------------	---

Description

Coverage of data by GSA and year (reporting the number of records)

Usage

```
FDI_coverage(data, MS, verbose = TRUE)
```

Arguments

data	data frame. One of the allowed FDI table among A, G, H, I, J
MS	Country
verbose	boolean. If TRUE a message is printed.

Value

the function returns a data frame reporting the coverage of the selected table in terms of number of records by country, GSA and year.

Author(s)

Vasiliki Sgardeli vsgard@hcmr.gr

Walter Zupa zupa@coispa.it

Examples

```
FDI_coverage(data = fdi_a_catch, MS = "PSP", verbose = FALSE)
FDI_coverage(data = fdi_h_spatial_landings, MS = "PSP", verbose = FALSE)
FDI_coverage(data = fdi_g_effort, MS = "PSP", verbose = FALSE)
```

FDI_cov_tableA

Check number of record in FDI A table

Description

The function checks and count the numbers of records data in the given table A grouped by year, GSA, MS, species, vessels length, and fishing techniques for three variables (Total live weight landed (ton), total value of landings (euro), and total discards (ton)). If SP, Vessel length, and fishing technique are not specified by the user the function combines those by default.

Usage

```
FDI_cov_tableA(
  data,
  MS,
  SP = "COMBINED",
  vessel_len = "COMBINED",
  fishtech = "COMBINED",
  GSA,
  verbose = TRUE
)
```

Arguments

data	FDI table A catch
MS	member state code
SP	species reference code in the three alpha code format ("COMBINED" values perform the analysis for all species present in data)
vessel_len	vessels length code ("COMBINED" values perform the analysis for all vessels length present in data)
fishtech	selected fishing techniques ("COMBINED" values perform the analysis for all fishing techniques present in data)
GSA	GSA code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list. The first element gives the summary table of records number. From the second to the fourth element gives 3 plots for each variables among: of total live weight landed, total value of landings (euro), and total discards (ton)).

Author(s)

Andrea Pierucci pierucci@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
FDI_cov_tableA(data = fdi_a_catch, SP = "MUT", MS = "PSP", GSA = "GSA99")
FDI_cov_tableA(
  data = fdi_a_catch, SP = "MUT", MS = "PSP",
  fishtech = unique(fdi_a_catch$fishing_tech), GSA = "GSA99"
)
FDI_cov_tableA(data = fdi_a_catch, SP = "MUT", MS = "PSP", GSA = "GSA99")
```

FDI_cov_tableG

Check FDI G table coverage

Description

The function counts the numbers of records and summarise data in the given table grouped by year, GSA, MS, vessels length, fishing techniques, and metier for the following 8 variables: Total days at sea; Total Fishing Days; Total kW days at Sea; total GT days at sea; Total kW fishing days; totgtfishdays; Hours at Sea; kW hours at sea; according to the [Fisheries Dependent Information data call 2021 - Annex 1](#) If Vessel length, fishing technique, and metier are not specified by the user the function combines those by default.

Usage

```
FDI_cov_tableG(
  data,
  MS,
  GSA,
  vessel_len = "COMBINED",
  fishtech = "COMBINED",
  met = "COMBINED",
  verbose = TRUE
)
```

Arguments

data	FDI table G effort
MS	member state code
GSA	GSA code
vessel_len	vessels length code ("COMBINED" values perform the analysis for all vessels length present in data)

fishtech	selected fishing techniques ("COMBINED" values perform the analysis for all fishing techniques present in data)
met	selected metiers ("COMBINED" values perform the analysis for all metiers present in data)
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list. The first element gives the summary table of records number. From the second to the ninth element gives 8 plots for each variables among:

- totseadays,
- totfishdays,
- totkwdaysatsea,
- totgtdaysatsea,
- totkwfishdays,
- totgfishdays,
- hrsea,
- kwhrsea

Author(s)

Andrea Pierucci pierucci@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
FDI_cov_tableG(data = fdi_g_effort, MS = "PSP", GSA = "GSA99")
FDI_cov_tableG(fdi_g_effort, MS = "PSP", GSA = "GSA99", fishtech = "DTS", met = "OTB_MDD_>=40_0_0")
```

FDI_cov_tableJ	<i>Check number of record in FDI J table</i>
----------------	--

Description

The function provides counts the numbers of records and generate summary of data in the given table grouped by year, GSA, MS, vessels length, and fishing techniques for the following 4 variables: total trips; total kW; total GT; total vessels.

Usage

```
FDI_cov_tableJ(
  data,
  MS,
  GSA,
  vessel_len = "COMBINED",
  fishtech = "COMBINED",
  verbose = TRUE
)
```

Arguments

data	FDI table J capacity
MS	member state code
GSA	GSA code
vessel_len	vessels length code ("COMBINED" values perform the analysis for all vessels length present in data)
fishtech	selected fishing techniques ("COMBINED" values perform the analysis for all fishing techniques present in data)
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list. The first element gives the summary table of records number. From the second to the fifth element gives 4 plots for each variables among:

- total trips;
- total kW;
- total GT;
- total vessels;

Author(s)

Andrea Pierucci pierucci@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
FDI_cov_tableJ(data = fdi_j_capacity, MS = "PSP", GSA = "GSA99")
FDI_cov_tableJ(data = fdi_j_capacity, MS = "PSP", GSA = "GSA99", fishtech = c("DTS", "PGP"))
```

FDI_cross_checks_AG *Cross check between FDI tables A and G*

Description

The function checks the possible data inconsistency between landings and effort.

Usage

```
FDI_cross_checks_AG(data1, data2, verbose = FALSE)
```

Arguments

data1	FDI table A catch
data2	FDI table G effort
verbose	boolean. If TRUE a message is printed.

Value

The function returns a table where all the mismatches between landings and effort are shown.

Author(s)

Andrea Pierucci pierucci@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
FDI_cross_checks_AG(data1 = fdi_a_catch, data2 = fdi_g_effort)
FDI_cross_checks_AG(fdi_a_catch, fdi_g_effort)
```

FDI_cross_checks_AH *Cross check between FDI tables A and H*

Description

The function checks the possible data inconsistency between landings in table A and spatial landings in table H.

Usage

```
FDI_cross_checks_AH(data1, data2, verbose = FALSE)
```

Arguments

data1	FDI catch table A
data2	FDI spatial landings table H
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list with two tables. In the first table all the mismatches between landings in table A and spatial landings in table H are shown, in the second table the comparison between total landings of table A and total spatial landings in table H is shown.

Author(s)

Andrea Pierucci pierucci@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
FDI_cross_checks_AH(data1 = fdi_a_catch, data2 = fdi_h_spatial_landings)
```

FDI_cross_checks_IG *Cross check between FDI tables I and G*

Description

The function checks the possible data inconsistency between spatial effort in table I and effort in table G.

Usage

```
FDI_cross_checks_IG(data1, data2, verbose = FALSE)
```

Arguments

data1	FDI spatial effort in table I
data2	FDI effort table G
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list with two tables. In the first table all the mismatches between spatial effort in table I and effort in table G are shown, in the second table the comparison between total spatial effort of table I and total effort in table G is shown.

Author(s)

Andrea Pierucci pierucci@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
FDI_cross_checks_IG(data1 = fdi_i_spatial_effort, data2 = fdi_g_effort)
```

FDI_cross_checks_JG *Cross check between FDI tables J and G*

Description

The function checks the possible data inconsistency between the amount of vessels in table J capacity and the amount of vessels in table G.

Usage

```
FDI_cross_checks_JG(data1, data2, verbose = FALSE)
```

Arguments

data1	FDI capacity in table J
data2	FDI effort table G
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list with all the mismatches between number of vessels in table J and G.

Author(s)

Andrea Pierucci pierucci@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
FDI_cross_checks_JG(data1 = fdi_j_capacity, data2 = fdi_g_effort, verbose = TRUE)
FDI_cross_checks_JG(fdi_j_capacity, fdi_g_effort)
```

FDI_disc_coverage	<i>Coverage of FDI discard data</i>
-------------------	-------------------------------------

Description

The functions checks the discard coverage in table A for the selected MS by GSAs.

Usage

```
FDI_disc_coverage(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	data frame of the FDI table A
MS	Country
GSA	GSA code
SP	species reference code in the three alpha code format.
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list of data frames by GSA reporting the landing volumes (with discard >0, =0 and =NK and total landing) by year

Author(s)

Vasiliki Sgardeli vsgard@hcmr.gr

Walter Zupa zupa@coispa.it

Examples

```
FDI_disc_coverage(fdi_a_catch, MS = "PSP", GSA = "GSA99", SP = "HKE", verbose = TRUE)
```

FDI_fishdays_cov	<i>Coverage comparison of totfishdays between FDI tables G and I</i>
------------------	--

Description

The function checks the comparison of totfishdays in FDI tables G and I

Usage

```
FDI_fishdays_cov(dataG, dataI, MS, verbose = TRUE)
```

Arguments

dataG	data frame of FDA table G
dataI	data frame of FDA table I
MS	country code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a data frame of the comparison of totfishdays between FDI tables G and I

Author(s)

Vasiliki Sgardeli vsgard@hcmr.gr

Walter Zupa zupa@coispa.it

Examples

```
FDI_fishdays_cov(dataG = fdi_g_effort, dataI = fdi_i_spatial_effort, MS = "PSP", verbose = TRUE)
```

fdi_g_effort	<i>fdi_g_effort in FDI DGMAREMED&BS datacall format</i>
--------------	---

Description

fdi_g_effort in FDI DGMAREMED&BS datacall format

Usage

```
fdi_g_effort
```

Format

An object of class `data.frame` with 2450 rows and 26 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

`fdi_h_spatial_land` *fdi_h_spatial_land* in FDI DGMAREMED&BS datacall format

Description

`fdi_h_spatial_land` in FDI DGMAREMED&BS datacall format

Usage

`fdi_h_spatial_land`

Format

An object of class `data.frame` with 5 rows and 23 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

`fdi_h_spatial_landings`
fdi_h_spatial_landings in FDI DGMAREMED&BS datacall format

Description

`fdi_h_spatial_landings` in FDI DGMAREMED&BS datacall format

Usage

`fdi_h_spatial_landings`

Format

An object of class `data.frame` with 2450 rows and 23 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

fdi_i_spatial_effort *fdi_i_spatial_effort in FDI DGMAREMED&BS datacall format*

Description

fdi_i_spatial_effort in FDI DGMAREMED&BS datacall format

Usage

fdi_i_spatial_effort

Format

An object of class data.frame with 2450 rows and 21 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

fdi_j_capacity *fdi_j_capacity in FDI DGMAREMED&BS datacall format*

Description

fdi_j_capacity in FDI DGMAREMED&BS datacall format

Usage

fdi_j_capacity

Format

An object of class data.frame with 2450 rows and 14 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

FDI_landweight_cov *Coverage of weight of landings in FDI table A and H*

Description

The functions checks the coverage of weight of landings comparing data reported in table A and H.

Usage

```
FDI_landweight_cov(dataA, dataH, MS, verbose = FALSE)
```

Arguments

dataA	data frame of the FDI table A
dataH	data frame of the FDI table H
MS	Country code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a data frame reporting the weight of landings by GSA and by year.

Author(s)

Vasiliki Sgardeli vsgard@hcmr.gr

Walter Zupa zupa@coispa.it

Examples

```
FDI_landweight_cov(dataA = fdi_a_catch, dataH = fdi_h_spatial_landings, MS = "PSP", verbose = TRUE)
```

FDI_prices_cov *Check prices trend in FDI A table*

Description

The function checks the trend prices in the given table grouped by year, GSA, MS, and species. If SP are not specified by the user the function combines those by default.

Usage

```
FDI_prices_cov(data, MS, SP = "COMBINED", GSA = "COMBINED", verbose = TRUE)
```

Arguments

data	FDI table A catch
MS	member state code
SP	species reference code in the three alpha code format ("COMBINED" values perform the analysis for all species present in data)
GSA	GSA code ("COMBINED" values perform the analysis for all GSAs present in data).
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list. The first element gives the summary table of records number. From the second to the fourth element gives 3 plots for each variables among: of total live weight landed, total value of landings (euro), and total discards (ton)).

Author(s)

Andrea Pierucci pierucci@coispa.eu

Walter Zupa zupa@coispa.it

Examples

```
FDI_prices_cov(data = fdi_a_catch, SP = c("MUT", "HKE"), MS = "PSP", GSA = "GSA99")
FDI_prices_cov(data = fdi_a_catch, SP = "MUT", MS = "PSP", GSA = "GSA99")
```

FDI_prices_not_null *Check of species value*

Description

The function estimates from the FDI table A an average price per species and year and compares it with average price calculated per country (by species). Furthermore, the function performs comparisons between total weight landings and total value landings. In particular it identifies the cases with total landings > 0 but landings value = 0. In case SP parameter is not specified, the analysis is conducted over all the species in the provided data frame.

Usage

```
FDI_prices_not_null(data, MS, GSA, SP = NA, verbose = FALSE)
```

Arguments

data	data frame of FDA table A catch.
MS	country code
GSA	GSA code
SP	vector of the species code for which the check should be performed
verbose	boolean. If TRUE a message is printed.

Value

the function returns a list of two data frames. The first one reports the prices comparison by species, while the second one reports the cases in which total landings > 0 but landings value = 0.

Author(s)

Vasiliki Sgardeli vsgard@hcmr.gr

Walter Zupa zupa@coispa.it

Examples

```
FDI_prices_not_null(  
  data = fdi_a_catch, MS = "PSP", GSA = "GSA99",  
  SP = c("ARA", "BOG", "HKE"), verbose = TRUE  
)
```

FDI_vessel_lenth	<i>Check of vessel lenght in FDI table J</i>
------------------	--

Description

The function checks the average length vessels with the vessel length category (table J)

Usage

```
FDI_vessel_lenth(data, MS, verbose = TRUE)
```

Arguments

data	data frame of table J
MS	country code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list of two data frames. The first reports the records with NAs in either vessel length or vessel category or both, while the second table reports the cases in which vessel length does not match vessel length category.

Author(s)

Vasiliki Sgardeli vsgard@hcmr.gr

Walter Zupa zupa@coispa.it

Examples

```
FDI_vessel_lenth(data = fdi_j_capacity, MS = "PSP", verbose = TRUE)
```

FDI_vessel_numbers *Check number of vessels in FDI table J and G*

Description

The function cross-checks the number of vessels in table J in comparison with the number reported in table G.

Usage

```
FDI_vessel_numbers(dataJ, dataG, MS, verbose = TRUE)
```

Arguments

dataJ	data frame of FDA table J catch.
dataG	data frame of FDA table G catch.
MS	country code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list of data frames. The first element reports the number of vessel in table J in comparison with table G and the relative difference percentage, while the second one reports the vessels not present in table G.

Author(s)

Vasiliki Sgardeli vsgard@hcmr.gr
 Walter Zupa zupa@coispa.it

Examples

```
FDI_vessel_numbers(dataJ = fdi_j_capacity, dataG = fdi_g_effort, MS = "PSP", verbose = TRUE)
```

GFCM_check_headers *Check headers of GFCM tables*

Description

Check headers of GFCM tables

Usage

```
GFCM_check_headers(data, table)
```

Arguments

data	data frame of data for the reference table
table	character, vector specifying the reference table. Allowed values: "task2.2", "task3", "task7.2", "task7.3.1", "task7.3.2"

Value

In case the data frame reports has the headers in the format of the RDBFIS database, it is returned back with the headers in the GFCM format adopted also by RDBqc package

GFCM_cov_II2	<i>Check coverage of GFCM task II.2 table</i>
--------------	---

Description

The function checks and count the numbers of records data in the given task II.2 table grouped by year, GSA, MS, species, and segment for two variables (Total landing (ton) and total discards (ton)). If SP and segment are not specified by the user the function combines those by default.

Usage

```
GFCM_cov_II2(
  data,
  MS,
  SP = "COMBINED",
  segment = "COMBINED",
  GSA,
  verbose = TRUE
)
```

Arguments

data	GFCM task II.2 table
MS	member state code
SP	species reference code in the three alpha code format ("COMBINED" values perform the analysis for all species present in data)
segment	segment code ("COMBINED" values perform the analysis for all segments present in data)
GSA	GSA code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list. The first element gives the summary table of records number. From the second to the third element gives 2 plots for total live landing and total discards (ton)).

Author(s)

Walter Zupa zupa@coispa.it

Examples

```
GFCM_cov_II2(data = task_ii2, MS = "ITA", GSA = "18", SP = "HKE", segment = "COMBINED")
```

GFCM_cov_task_iii *Check number of individuals in GFCM Task III table*

Description

The function checks the consistencies of the total number of individual caught in comparison with the sum of the individuals alive, dead and released reported in Task III table.

Usage

```
GFCM_cov_task_iii(data, MS, GSA, SP = "COMBINED", verbose = TRUE)
```

Arguments

data	Task III table
MS	member state code
GSA	GSA code
SP	species reference code in the three alpha code format ("COMBINED" values perform the analysis for all species present in data)
verbose	boolean. If TRUE a message is printed.

Value

The function returns a list. The first element is a table reporting the inconsistencies of the total individual caught in comparison to the sum of the individuals alive, dead and released. The second element of the list is a plot of the time series of the individuals caught by year, source, and gear.

Author(s)

Walter Zupa zupa@coispa.it

Examples

```
GFCM_cov_task_iii(
  data = task_iii, SP = "Dasyatis pastinaca",
  MS = "ITA", GSA = "18"
)
```

GP_tab_example *GP table in MED&BS datacall format*

Description

GP table in MED&BS datacall format

Usage

```
GP_tab_example
```

Format

An object of class `data.frame` with 12 rows and 22 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

GSAlist

GSAlist table

Description

GSAlist table

Usage

GSAlist

Format

An object of class `data.frame` with 22 rows and 2 columns.

Author(s)

Walter Zupa <zupa@fondazionecoispa.org>

Landing_tab_example

Landing table in MED&BS datacall format

Description

Landing table in MED&BS datacall format

Usage

Landing_tab_example

Format

An object of class `data.frame` with 57 rows and 114 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

MA_tab_example	<i>MA table in MED&BS datacall format</i>
----------------	---

Description

MA table in MED&BS datacall format

Usage

MA_tab_example

Format

An object of class `data.frame` with 71 rows and 11 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

MEDBSSP	<i>MEDBSSP table</i>
---------	----------------------

Description

MEDBSSP table

Usage

MEDBSSP

Format

An object of class `data.frame` with 63 rows and 1 columns.

Author(s)

Alessandro Mannini <alessandro.mannini@irbim.cnr.it>

MEDBS_ALK *Plot of Age-Length Keys*

Description

The function allows to check the data in the ALK table providing plots by sex for a selected species

Usage

```
MEDBS_ALK(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	ALK table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned.

Value

a list of ALK plots by sex is return.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_ALK(data = ALK_tab_example, SP = "MUT", MS = "ITA", GSA = "GSA 99")
```

MEDBS_ALK_MLAA *Plot of Age-Length Keys*

Description

The function allows to check the data in the ALK table providing plots of the mean length by age by sex for a selected species

Usage

```
MEDBS_ALK_MLAA(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	ALK table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned.

Value

a list of ALK plots by sex is return.

Author(s)

Isabella Bitetto bitetto@fondazionecoispa.org

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_ALK_MLAA(data = ALK_tab_example, SP = "MUT", MS = "ITA", GSA = "GSA 99")
```

MEDBS_ALK_NB	<i>Check on numbers in ALK</i>
--------------	--------------------------------

Description

The function allows to verify the numbers of individuals in the ALK table by sex and age for a selected species

Usage

```
MEDBS_ALK_NB(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	ALK table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned.

Value

a list of records with mismatches is return.

Author(s)

Isabella Bitetto bitetto@fondazionecoispa.org

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_ALK_NB(data = ALK_tab_example, SP = "MUT", MS = "ITA", GSA = "GSA 99")
```

MEDBS_Catch_CAA *Numbers-at-age plot from Catch table (Landings vs Discards)*

Description

Builds a multi-panel numbers-at-age plot from the MED&BS Catch table. Age-specific counts are extracted from AGE_* columns (landed and discard), quarters are summed, and results are displayed as grouped barplots (Landing vs Discard) by **YEAR** (columns) and **GEAR-MESH-FISHERY group** (rows). Strip labels are displayed only on the outer margins using **HH**.

Usage

```
MEDBS_Catch_CAA(data, SP, MS, GSA, verbose = TRUE, embedded = TRUE)
```

Arguments

data	A data.frame in MED&BS Catch datacall format.
SP	Species code (character).
MS	Member State code (character).
GSA	GSA code (character), e.g. "GSA 20".
verbose	Logical; if TRUE prints informative messages.

Details

The function:

1. filters by AREA/COUNTRY/SPECIES;
2. cleans AGE_* columns (NA and -1 set to 0);
3. reshapes to long format and aggregates (quarters summed);
4. plots numbers-at-age as grouped bars (Landing vs Discard);
5. applies outer strips/scales through HH: :useOuterScales().

Value

A trellis object (lattice) or NULL if no data are available after filtering/cleaning.

Author(s)

Walter Zupa

Examples

```
## Not run:
p <- MEDBS_Catch_CAA(data = Catch_tab_example, SP = "ANE", MS = "GRC", GSA = "GSA 20")
print(p)

## End(Not run)
```

MEDBS_Catch_coverage *Check the coverage of Catch table*

Description

The function allows to check the coverage of Catch table by mean of summary tables summarizing both landing and discard volumes and producing relative plots for the selected species.

Usage

```
MEDBS_Catch_coverage(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	Catch table in MEDBS format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns two summary tables: one for landing coverage and the other for discard coverage. Furthermore, plots of landings and discards by gear are also returned

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_Catch_coverage(Catch_tab_example, "DPS", "ITA", "GSA 9")
```

MEDBS_Catch_LW *check the length-weight consistency in the Catch table*

Description

check the length-weight consistency in the Catch table

Usage

```
MEDBS_Catch_LW(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	Catch table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

the function returns a plot with the lengths and weights from the Catch table by year.

Author(s)

Isabella Bitetto bitetto@fondazionecoispa.org

Examples

```
MEDBS_Catch_LW(data = Catch_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_check_disaggregated

Check for disaggregated data rows in landings, discards and catch tables

Description

The function checks the presence of disaggregated data (same stratum but with different volumes of landings and discards) rows in MED & BS landings, discards and catch tables.

Usage

```
MEDBS_check_disaggregated(data, type = "l", SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing either landings, discards or catch data
type	string vector indicating the type of table to be checked. "l" for landing; "d" for discards; "c" for catch table.
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame containing the disaggregated rows to be likely aggregated in the data.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Loredana Casciaro casciaro@coispa.eu

Examples

```
MEDBS_check_disaggregated(
  data = Discard_tab_example, type = "d", SP = "DPS",
  MS = "ITA", GSA = "GSA 9", verbose = TRUE
)
MEDBS_check_disaggregated(
  data = Landing_tab_example, type = "l", SP = "DPS",
  MS = "ITA", GSA = "GSA 9", verbose = TRUE
)
MEDBS_check_disaggregated(
  data = Catch_tab_example, type = "c", SP = "DPS",
  MS = "ITA", GSA = "GSA 9", verbose = TRUE
)
```

MEDBS_check_duplicates

Check for duplicated data rows in MED & BS tables

Description

The function checks the presence of duplicated rows in MED & BS tables data.

Usage

```
MEDBS_check_duplicates(data, type = "l", SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing either landings, discards or catch data
type	string vector indicating the type of table to be checked. "l" for landing; "d" for discards; "c" for catch table; "gp" for growth parameters table; "alk" for age-length keys table; "ma" for maturity at age table; "ml" for maturity at length table; "sra" for sex ratio at age table; "srl" for maturity at length table..
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame containing the duplicated rows to be likely deleted from the data.

Author(s)Alessandro Mannini alessandro.mannini@ec.europa.euWalter Zupa zupa@coispa.it**Examples**

```

MEDBS_check_duplicates(
  data = Discard_tab_example, type = "d", SP = "DPS",
  MS = "ITA", GSA = "GSA 9", verbose = TRUE
)
MEDBS_check_duplicates(
  data = Landing_tab_example, type = "l", SP = "DPS",
  MS = "ITA", GSA = "GSA 9", verbose = TRUE
)
MEDBS_check_duplicates(
  data = Catch_tab_example, type = "c", SP = "DPS",
  MS = "ITA", GSA = "GSA 9", verbose = TRUE
)

```

MEDBS_check_missing_years

Check for missing years in MED & BS tables

Description

The function checks the presence of missing years in MED & BS tables data.

Usage

```

MEDBS_check_missing_years(
  data,
  end_year,
  type = "l",
  SP,
  MS,
  GSA,
  verbose = TRUE
)

```

Arguments

data	data frame containing either landings, discards or catch data
end_year	numeric value reporting the final year of the time series for the given country
type	string vector indicating the type of table to be checked. "l" for landing; "d" for discards; "c" for catch table.
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a vector containing the missing years in data. NULL is returned in case no data were available for the selected combination of country, GSA and species. A vector of length 0 is returned in case there are no missing years in the data.

Author(s)

Walter Zupa zupa@coispa.it

Examples

```
df <- Discard_tab_example[-which(Discard_tab_example$year==2011),]
MEDBS_check_missing_years(
  data = df, end_year=2002, type = "d", SP = "DPS",
  MS = "ITA", GSA = "GSA 9", verbose = TRUE
)
```

MEDBS_comp_disc_YQ *Comparison between discards in weight by quarter and -1*

Description

The function compares the discards weights aggregated by quarter and by year for a selected species at gear level.

Usage

```
MEDBS_comp_disc_YQ(data, MS, GSA, SP, verbose = FALSE)
```

Arguments

data	data frame containing discards data
MS	member state code
GSA	GSA code (Geographical sub-area)
SP	species code
verbose	boolean. If TRUE a message is printed.

Value

The function returns a data frame with the comparison of discards aggregated by quarters and by year

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_comp_disc_YQ(data = Discard_tab_example, MS = "ITA", GSA = "GSA 9", SP = "DPS")
```

MEDBS_comp_disc_YQ_fishery

Comparison between discards in weight by quarter, quarter -1 and by fishery

Description

The function allow to estimates the discards in weight for a selected species by quarter and fishery

Usage

```
MEDBS_comp_disc_YQ_fishery(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing discards data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame with the comparison of discards aggregated by quarters and by year and fishery

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_comp_disc_YQ_fishery(data = Discard_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_comp_land_Q_VL *Comparison between landings in weight by quarter accounting for vessel length*

Description

The function allows to perform the comparison of landings of a selected species aggregated by quarters, accounting for the presence of vessel length

Usage

```
MEDBS_comp_land_Q_VL(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame for the comparison of landings aggregated by quarters, accounting for the presence of vessel length information.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_comp_land_Q_VL(data = Landing_tab_example, MS = "ITA", GSA = "GSA 9", SP = "DPS")
```

MEDBS_comp_land_Q_VL_fishery

Comparison between landings in weight by quarter and fishery, accounting for vessel length

Description

The function performs the comparison of landings of a selected species aggregated by quarters and fishery, accounting for the presence of vessel length

Usage

```
MEDBS_comp_land_Q_VL_fishery(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame for the comparison of landings aggregated by quarters and fishery accounting for the presence of vessel length information.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_comp_land_Q_VL_fishery(data = Landing_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_comp_land_YQ *Comparison between landings in weight by quarter and -1*

Description

The function allows to perform the comparison of landings of a selected species aggregated by quarters and by year

Usage

```
MEDBS_comp_land_YQ(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame for the comparison of landings aggregated by quarters and by year

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_comp_land_YQ(data = Landing_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_comp_land_YQ_fishery

Comparison between landings in weight by quarter, quarter -1 and by fishery

Description

The function allows to perform the comparison of landings of a selected species aggregated by quarters, and by year and fishery

Usage

```
MEDBS_comp_land_YQ_fishery(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame for the comparison of landings aggregated by quarters, and by year and fishery

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_comp_land_YQ_fishery(data = Landing_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_discard_coverage

Check the coverage of discard data

Description

The function allows to check the coverage of the time series in discard table for a selected species.

Usage

```
MEDBS_discard_coverage(Discard_tab, SP, MS, GSA, verbose = TRUE)
```

Arguments

Discard_tab	Discard table in MED&BS format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

A summary table and a plot of discard time series by year and gear are returned.

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_discard_coverage(Discard_tab_example, "DPS", "ITA", "GSA 9")
```

```
MEDBS_disc_mean_weight
```

Check of mean discard weight aggregations by year, gear and fishery

Description

The function allows to check consistency of mean discard of a selected species plotting the discards' weight by year, gear and fishery

Usage

```
MEDBS_disc_mean_weight(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing discards data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a plot of the mean discards weight by year, gear and fishery aggregation

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_disc_mean_weight(data = Discard_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_GP_check

Check of growth parameters table

Description

The function checks the growth parameters by sex and year for a selected species

Usage

```
MEDBS_GP_check(data, SP, MS, GSA, verbose = FALSE, all_plots = FALSE)
```

Arguments

data	growth parameters table in MED&BS data call format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned
all_plots	boolean. If TRUE all plots are generated; if FALSE only plots used in the Rmd chunk are generated

Value

A list of objects containing a summary table and different plots of the growth curves by sex and year is returned by the function.

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_GP_check(GP_tab_example, "MUT", "ITA", "GSA 18")
```

MEDBS_ks	<i>Kolmogorov-Smirnov test</i>
----------	--------------------------------

Description

The function allows to perform the Kolmogorov-Smirnov test on both landings and discards for a selected species providing cumulative length distribution plots by fishery and year. The function performs Kolmogorov-Smirnov tests on couples of years to assess if they belong to the same population.

Usage

```
MEDBS_ks(data, type, SP, MS, GSA, Rt = 1, verbose = TRUE)
```

Arguments

data	data frame of either landings or discards data
type	type of data frame. "l" for landing and "d" for discard
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
Rt	ratio to be applied to subsample data to reduce the risk of rejection of H0 Hypothesis
verbose	boolean. If TRUE messages are returned

Value

the function returns a list of data frames and cumulative distribution plots

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_ks(data = Landing_tab_example, type = "l", SP = "DPS", MS = "ITA", GSA = "GSA 9", Rt = 1)
```

MEDBS_Landing_coverage

Check the coverage of Landing table

Description

The function allows to check the coverage in landing table providing a summary table and a plot of landing.

Usage

```
MEDBS_Landing_coverage(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	Landing table in MED&BS format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

A list containing a summary table and coverage plot is provided.

Examples

```
MEDBS_Landing_coverage(Landing_tab_example, "DPS", "ITA", "GSA 9")
```

MEDBS_land_mean_weight

Mean weight by year, gear and fishery aggregation

Description

The function allows to check consistency of mean landing of a selected species plotting the landings' weight by year, gear and fishery

Usage

```
MEDBS_land_mean_weight(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a plot of the mean landing weight by year, gear and fishery aggregation, and returns the data frame as well.

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_land_mean_weight(data = Landing_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_lengthclass_0 *Checks length classes numbers with zeros in landings and discards*

Description

The function checks landings and discards for the presence of length class filled in having weight > 0.

Usage

```
MEDBS_lengthclass_0(data, type = "l", SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing or discards data
type	string vector indicating the type of table to be checked. "l" for landing; "d" for discards.
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame with the rows with 0 values length class having weight > 0.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```

MEDBS_lengthclass_0(
  data = Landing_tab_example, type = "l",
  SP = "DPS", MS = "ITA", GSA = "GSA 9", verbose = TRUE
)
MEDBS_lengthclass_0(
  data = Discard_tab_example, type = "d", SP = "DPS",
  MS = "ITA", GSA = "GSA 9", verbose = TRUE
)

```

MEDBS_length_ind *Main length size indicators*

Description

The function allows to check the consistency of length data for a selected species on both landings and discards: Main length size indicators. The function keeps the same calculations and checks of the original implementation, but it returns a single combined time series plot (instead of multiple plots).

Usage

```

MEDBS_length_ind(
  data,
  type,
  SP,
  MS,
  GSA,
  splines = c(0.2, 0.4, 0.6, 0.8),
  Xtresholds = c(0.25, 0.5, 0.75),
  verbose = TRUE,
  embedded = FALSE
)

```

Arguments

data	data frame of either landings or discards data
type	type of data frame. "l" for landing and "d" for discard
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
splines	spline values assignment to fit cumulative distributions
Xtresholds	threshold value
verbose	boolean. If TRUE messages are returned
embedded	boolean. If TRUE, the function generates only Min, Median and Max in a single combined plot. If FALSE, the combined plot includes also Mean, 25th and 75th percentiles.

Value

The function returns a list containing a summary table and a combined plot of length indicators.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_length_ind(Landing_tab_example,
  type = "l", SP = "DPS", MS = c("ITA"),
  GSA = c("GSA 9"), splines = c(0.2, 0.4, 0.6, 0.8),
  Xtresholds = c(0.25, 0.5, 0.75), embedded = FALSE
)
MEDBS_length_ind(Discard_tab_example,
  type = "d", SP = "DPS", MS = c("ITA"),
  GSA = c("GSA 9"), splines = c(0.2),
  Xtresholds = c(0.5), embedded = TRUE
)
```

MEDBS_LFD

LFD of MED & BS landing and discard data

Description

The function allows to report the observed Length Frequency Distributions of a selected species.

Usage

```
MEDBS_LFD(data, data2, type, SP, MS, GSA, OUT = FALSE, verbose = FALSE)
```

Arguments

data	data frame of either landings or discards data
data2	data frame of discards data, only in case type="b"
type	type of data frame. "l" for landing, "d" for discard and "b" for both the data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
OUT	boolean. If TRUE outputs are saved in the OUTPUT folder
verbose	boolean. If TRUE messages are returned

Value

The function returns different data frame and plots of LFD of Landing, Discards and Catches according to the source data used in the analysis.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_LFD(data=RDBqc::Landing_tab_example,  
data2=RDBqc::Discard_tab_example, type="b",  
SP="DPS", MS="ITA", GSA="GSA 9", OUT=TRUE, verbose = TRUE)
```

MEDBS_LW_check

Check LW parameters in GP table

Description

The function checks the length-weight parameters included in the GP table for a selected species.

Usage

```
MEDBS_LW_check(data, SP, MS, GSA, verbose = FALSE)
```

Arguments

data	growth params table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

A summary table and plots of the LW parameters are returned by the function.

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_LW_check(GP_tab_example, "MUT", "ITA", "GSA 18")
```

MEDBS_MA_check	<i>Check of MA_tab (maturity at age) table</i>
----------------	--

Description

The function checks the maturity at age (MA) table providing a summary table of the data coverage and plots for the selected species of the proportion of matures for age class by sex and year.

Usage

```
MEDBS_MA_check(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	maturity at AGE table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

A summary table and plots are returned by the function.

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_MA_check(MA_tab_example, "DPS", "ITA", "GSA 99")
```

MEDBS_ML_check	<i>Check of ML_tab (maturity at length) table</i>
----------------	---

Description

The function checks the maturity at length (ML) table providing a summary table of the data coverage and plots for the selected species of the proportion of matures for age class by sex and year.

Usage

```
MEDBS_ML_check(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	maturity at length table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

a summary table and plots

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_ML_check(ML_tab_example, "DPS", "ITA", "GSA 99")
```

MEDBS_plot_discard_ts *Plot of total discards*

Description

The function estimates the total discard time series by both year and quarters for a selected combination of member state, GSA and species.

Usage

```
MEDBS_plot_discard_ts(data, SP, MS, GSA, by = "year")
```

Arguments

data	data frame containing discard data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
by	string defining the temporal aggregation level of discard data to be plotted. Allowed values are: "year" and "quarter"

Value

The function returns a plot of the total discard time series by year or by quarters. The plot by year also reports the landing by gear.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_plot_discard_ts(  
  data = Discard_tab_example, SP = "DPS",  
  MS = "ITA", GSA = "GSA 9", by = "quarter"  
)  
MEDBS_plot_discard_ts(  
  data = Discard_tab_example, SP = "DPS",  
  MS = "ITA", GSA = "GSA 9", by = "year"  
)
```

MEDBS_plot_disc_vol *Plot of total discards by gear and fishery*

Description

The function allows to visual check the time series of discard volumes by fishery of a selected species

Usage

```
MEDBS_plot_disc_vol(data, SP, MS, GSA)
```

Arguments

data	data frame containing discard data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)

Value

The function returns a plot of the total discards time series by fishery and gear

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_plot_disc_vol(data = Discard_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_plot_landing_ts *Plot of total landing time series*

Description

The function estimates the total landings time series by both year and quarters for a selected combination of member state, GSA and species.

Usage

```
MEDBS_plot_landing_ts(data, SP, MS, GSA, by = "year", verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
by	string defining the temporal aggregation level of landing data to be plotted. Allowed values are: "year" and "quarter"
verbose	boolean. If TRUE messages are returned

Value

The function returns a plot of the total landing time series by year or by quarters. The plot by year also reports the landing by gear.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_plot_landing_ts(  
  data = Landing_tab_example, SP = "DPS",  
  MS = "ITA", GSA = "GSA 9", by = "quarter"  
)  
MEDBS_plot_landing_ts(  
  data = Landing_tab_example, SP = "DPS", MS = "ITA",  
  GSA = "GSA 9", by = "year"  
)
```

MEDBS_plot_land_vol *Plot of total landing by gear and fishery*

Description

The function checks the time series of landing volumes by fishery of a selected species

Usage

```
MEDBS_plot_land_vol(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data frame containing landing data
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a plot of the total landing time series by fishery and gear

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Isabella Bitetto bitetto@coispa.it

Examples

```
MEDBS_plot_land_vol(data = Landing_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9")
```

MEDBS_SA_check *Check of SA_tab (sex ratio at age) table*

Description

The function allows to check the sex ratio at age (SA) table providing a summary table of the data coverage and plots for the selected species of the proportion of sex ratio for age class by year.

Usage

```
MEDBS_SA_check(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	sex ratio at age table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

a summary table and plots

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_SA_check(SA_tab_example, "DPS", "ITA", "GSA 99")
```

MEDBS_SL_check

Check of SL_tab (sex ratio at length) table

Description

The function allows to check the sex ratio at length (SL) table providing a summary table of the data coverage and plots for the selected species of the proportion of sex ratio for length class by year.

Usage

```
MEDBS_SL_check(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	sex ratio at length table in MED&BS data call format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

a summary table and plots

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_SL_check(SL_tab_example, "DPS", "ITA", "GSA 99")
```

MEDBS_SOP

check of the sum of products

Description

check of the sum of products

Usage

```
MEDBS_SOP(data, SP, MS, GSA, threshold = 5, verbose = TRUE)
```

Arguments

data	Catch table in MED&BS datacall format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
threshold	threshold value in percentage to check the percentage difference between SOP and both volumes of landing and discard. Default value is 5%
verbose	boolean. If TRUE messages are returned

Value

the function returns a data frame of the record with values of percentage difference between SOP and both volumes of landing and discard greater then threshold value.

Author(s)

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_SOP(data = Catch_tab_example, SP = "DPS", MS = "ITA", GSA = "GSA 9", threshold = 5)
```

MEDBS_weight_0 *Check of weights 0 in landings and discards*

Description

The function checks landings or discards in weight equal to 0 having length classes filled in

Usage

```
MEDBS_weight_0(data, type = "l", SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data.table object containing landing or discard data
type	type of table: "l" for landings; "d" for discards
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a table of rows with 0 values in weights having length classes filled in.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_weight_0(  
  data = Landing_tab_example, type = "l",  
  SP = "DPS", MS = "ITA", GSA = "GSA 9", verbose = TRUE  
)  
MEDBS_weight_0(  
  data = Discard_tab_example, type = "d", SP = "DPS",  
  MS = "ITA", GSA = "GSA 9", verbose = TRUE  
)
```

MEDBS_weight_minus1 *Check weights -1 in landings*

Description

The function checks landings in weight equal to -1 having length class filled in

Usage

```
MEDBS_weight_minus1(data, type = "l", SP, MS, GSA, verbose = TRUE)
```

Arguments

data	data.table object containing landing or discards data
type	type of table: "l" for landings; "d" for discards
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned.

Value

The function returns a table of rows with -1 values in landing weights having length class filled in.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_weight_minus1(  
  data = Landing_tab_example, type = "l",  
  SP = "DPS", MS = "ITA", GSA = "GSA 9", verbose = TRUE  
)  
MEDBS_weight_minus1(  
  data = Discard_tab_example, type = "d", SP = "DPS",  
  MS = "ITA", GSA = "GSA 9", verbose = TRUE  
)
```

MEDBS_yr_missing_length

Years with missing length distributions

Description

The function checks the presence of years with missing length distributions in both landings and discards for a selected species.

Usage

```
MEDBS_yr_missing_length(data, type, SP, MS, GSA, verbose = FALSE)
```

Arguments

data	data frame of landings or discards data
type	type of data frame. "l" for landing and "d" for discard
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

The function returns a data frame containing the reference combination of year, gear and fishery missing length distributions.

Author(s)

Alessandro Mannini alessandro.mannini@ec.europa.eu

Walter Zupa zupa@coispa.it

Examples

```
MEDBS_yr_missing_length(  
  data = Discard_tab_example, type = "d",  
  SP = "DPS", MS = "ITA", GSA = "GSA 9"  
)  
MEDBS_yr_missing_length(  
  data = Landing_tab_example, type = "l", SP = "DPS",  
  MS = "ITA", GSA = "GSA 9"  
)
```

minmaxLtaskVII2 *minmaxLtaskVII2 in GFCM datacall format*

Description

minmaxLtaskVII2 in GFCM datacall format

Usage

minmaxLtaskVII2

Format

An object of class `data.frame` with 26 rows and 3 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

minmaxLtaskVII31 *minmaxLtaskVII31 in GFCM datacall format*

Description

minmaxLtaskVII31 in GFCM datacall format

Usage

minmaxLtaskVII31

Format

An object of class `data.frame` with 36 rows and 4 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

ML_tab_example	<i>ML table in MED&BS datacall format</i>
----------------	---

Description

ML table in MED&BS datacall format

Usage

ML_tab_example

Format

An object of class `data.frame` with 437 rows and 12 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

RCG_check_AL	<i>Check consistency of age-length relationship</i>
--------------	---

Description

The function checks the consistency of the age-length data included in the table of RCG detailed data. Furthermore, the function identifies the age data outside a reference range of values provided by the user for the species. In case the `min_age` and `max_age` parameters are not provided, the function tests the lowest and the higher values of Age as outliers by mean of the Grubbs' test (from package outliers)

Usage

```
RCG_check_AL(data, MS, GSA, SP, min_age = NA, max_age = NA, verbose = TRUE)
```

Arguments

<code>data</code>	table of detailed data in RCG format
<code>MS</code>	member state code
<code>GSA</code>	GSA code (Geographical sub-area)
<code>SP</code>	species code
<code>min_age</code>	minimum age expected
<code>max_age</code>	maximum age expected
<code>verbose</code>	boolean. If TRUE messages are returned

Value

The function returns a list of object containing a summary table, an age-length plot and a table of the outliers, if any.

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

References

Grubbs, F.E. (1950). Sample Criteria for testing outlying observations. *Ann. Math. Stat.* 21, 1, 27-58

Examples

```
RCG_check_AL(
  data = data_ex, MS = "ITA", GSA = "GSA99",
  SP = "Mullus barbatus", min_age = 0, max_age = 9
)
RCG_check_AL(data = data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

 RCG_check_CL

Quality checks on CL RCG table

Description

The function checks CL tables for temporal, spatial, species and metier coverage

Usage

```
RCG_check_CL(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	Landing table in RCG CL format
MS	member state code
GSA	GSA code (Geographical sub-area)
SP	species code
verbose	boolean. If TRUE messages are returned

Value

The output is a list of 6 data frames:

1. Sum of Landings by year, quarter and month;
2. Sum of Landing value by year, quarter and month;
3. Sum of landings by LandCtry, VslFlgCtry, Area, Rect, SubRect, Harbour;
4. Sum of landing value by LandCtry, VslFlgCtry, Area, Rect, SubRect, Harbour;
5. Sum of landings by Year, Species, fishing_activity_category_national, fishing_activity_category_eu_l6;
6. Sum of landing value by Year, Species, fishing_activity_category_national, fishing_activity_category_eu_l6.

Author(s)Isabella Bitetto bitetto@coispa.itWalter Zupa zupa@coispa.it**Examples**

```
RCG_check_CL(data_exampleCL, MS = "COUNTRY1", GSA = "GSA99", SP = "Parapenaeus longirostris")
```

RCG_check_LFD

*Consistency check of LFDs***Description**

The function allows to check the consistency of LFDs (length frequency distributions) by year on a given species generating a multi-frame plot. The function also returns the records in which the length classes are greater or lower than the expected ones (`min_len` and `max_len` parameters).

Usage

```
RCG_check_LFD(data, SP, MS, GSA, min_len = NA, max_len = NA, verbose = TRUE)
```

Arguments

<code>data</code>	RCG CS table
<code>SP</code>	species code
<code>MS</code>	member state code
<code>GSA</code>	GSA code (Geographical sub-area)
<code>min_len</code>	minimum length
<code>max_len</code>	maximum length
<code>verbose</code>	boolean. If TRUE messages are returned

Value

The function returns a comparison plot of LFDs among the years and a table reporting the length classes out of the expected range, according to the reference length provided.

Author(s)Isabella Bitetto bitetto@coispa.itWalter Zupa zupa@coispa.it**Examples**

```
RCG_check_LFD(
  data = data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus",
  min_len = 30, max_len = 300
)
RCG_check_LFD(
  data = data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus",
  min_len = NA, max_len = NA
)
```

`RCG_check_LFD_comm_cat`*Check consistency of LFD by year and commercial category*

Description

The function allows to check the consistency of LFDs (length frequency distributions) by year and commercial size category on a given species.

Usage

```
RCG_check_LFD_comm_cat(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

<code>data</code>	RCG CS table
<code>SP</code>	species code
<code>MS</code>	member state code
<code>GSA</code>	GSA code (Geographical sub-area)
<code>verbose</code>	boolean. If TRUE messages are returned

Value

The function returns a multi-frame plot of LFDs (length frequency distributions) by year and commercial size category for the selected species. The function also returns a data frame with the length range by year and commercial size category.

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
RCG_check_LFD_comm_cat(data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

`RCG_check_loc`*Check trip location*

Description

The function allows to check the spatial distribution of data using the initial and final coordinates, where available, and the ports position included in the data in case coordinates are not available.

Usage

```
RCG_check_loc(data, MS = NA, GSA = NA, ports = circabc)
```

Arguments

data	detailed data in RCG CS format
MS	member state code
GSA	GSA code
ports	ports codification file

Value

A map of trip locations is generated.

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
RCG_check_loc(data_ex)
```

RCG_check_lw

Consistency check of length-weight relationship

Description

The function allows to check the consistency of length-weight relationship by sex and year on a given species generating a multi-frame plot. The function also returns the records in which the individual weights are greater or lower than the expected ones (Min and Max parameters). In case the Min and Max parameters are not provided, the function tests the lowest and the higher values of individual weights as outliers by mean of the Grubbs' test (from package outliers)

Usage

```
RCG_check_lw(data, SP, MS, GSA, Min = NA, Max = NA, verbose = TRUE)
```

Arguments

data	table of detailed data in RCG format
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
Min	min weight expected in the data
Max	max weight expected in the data
verbose	boolean. If it is TRUE messages are reported with the outputs

Value

Plot and error message

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

References

Grubbs, F.E. (1950). Sample Criteria for testing outlying observations. *Ann. Math. Stat.* 21, 1, 27-58

Examples

```
RCG_check_lw(data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus", Min = 0, Max = 1000)
RCG_check_lw(data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

RCG_check_mat

Check consistency sex and maturity stage

Description

The function allows to perform a visual check of the maturity stage composition by length class, sex and year.

Usage

```
RCG_check_mat(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	table of detailed data in RCG format
MS	member state code
GSA	GSA code
SP	reference species for the analysis
verbose	boolean. If it is TRUE messages are reported with the outputs

Value

The function the returns the plot of the maturity stages by length class

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
RCG_check_mat(data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

RCG_check_mat_ogive *check_mat_ogive*

Description

The function allows to check the maturity stages composition estimating the maturity ogives by sex for the selected species, using a selected pool of stages to classify the immature stages in the sample.

Usage

```
RCG_check_mat_ogive(  
  data,  
  MS,  
  GSA,  
  SP,  
  sex,  
  immature_stages = c("0", "1", "2a"),  
  verbose = TRUE  
)
```

Arguments

data	table of detailed data in RCG format
MS	member state code
GSA	GSA code (Geographical sub-area)
SP	species code
sex	defines the sex of the individuals selected for the analysis ('F' for females, 'M' for males)
immature_stages	vector of maturity stages considered immature
verbose	boolean. If TRUE messages are returned

Value

Plot ogive by sex

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
RCG_check_mat_ogive(data_ex,  
  MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus",  
  sex = "F", immature_stages = c("0", "1", "2a")  
)
```

 RCG_summarize_ind_meas

Number of individual by trip for which biological data have been collected (length, sex, maturity, weight and age)

Description

Number of individual by trip for which biological data have been collected (length, sex, maturity, weight and age)

Usage

```
RCG_summarize_ind_meas(data, MS, GSA, SP, verbose = TRUE)
```

Arguments

data	detailed data in RCG CS format
MS	member state code
GSA	GSA code
SP	species reference code in the three alpha code format
verbose	boolean value to obtain further explanation messages from the function

Value

The function returns a table containing a summary of measurements by trip for each biological variable

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
RCG_summarize_ind_meas(data = data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

 RCG_summarize_trips *summarizing the number of trips/hauls monitored by year by port, metier, sampling method;*

Description

The function allows to summarise monitored by year by port, metier, sampling method

Usage

```
RCG_summarize_trips(data, SP, MS, GSA, verbose = TRUE)
```

Arguments

data	RCG CS table
SP	species code
MS	member state code
GSA	GSA code (Geographical sub-area)
verbose	boolean. If TRUE messages are returned

Value

Number of trips by area, year, port, metier and sampling method

Author(s)

Isabella Bitetto bitetto@coispa.it

Walter Zupa zupa@coispa.it

Examples

```
RCG_summarize_trips(data_ex, MS = "ITA", GSA = "GSA99", SP = "Mullus barbatus")
```

read.coded.file	<i>Read encoded data</i>
-----------------	--------------------------

Description

Read encoded data

Usage

```
read.coded.file(file, sep = ",", dec = ".", verbose = FALSE)
```

Arguments

file	file path of the table to be read
sep	separator of the csv file (es. ";", ",", ")")
dec	decimals separator of the csv file (es. ".", ",")
verbose	boolean. Returns messages if TRUE.

Value

The function returns the csv auto-selecting the best encoding to be used. It is possible to set both the value and the decimar separators

Examples

```
## when fill = TRUE
test1 <- data.frame(a=1:5, b=c("a","b","c","d","e"))
tf <- tempfile()
write.table(test1, tf, sep=";", row.names=FALSE)
read.coded.file(tf, verbose=TRUE)
```

SA_tab_example	<i>SA table in MED&BS datacall format</i>
----------------	---

Description

SA table in MED&BS datacall format

Usage

SA_tab_example

Format

An object of class `data.frame` with 74 rows and 9 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

sex_mat	<i>sex_mat in GFCM datacall format</i>
---------	--

Description

sex_mat in GFCM datacall format

Usage

sex_mat

Format

An object of class `spec_tbl_df` (inherits from `tbl_df`, `tbl`, `data.frame`) with 42 rows and 5 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

SL_tab_example	<i>SL table in MED&BS datacall format</i>
----------------	---

Description

SL table in MED&BS datacall format

Usage

SL_tab_example

Format

An object of class `data.frame` with 454 rows and 10 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

SSPP	<i>SSPP table</i>
------	-------------------

Description

SSPP table

Usage

SSPP

Format

An object of class `data.frame` with 13417 rows and 8 columns.

Author(s)

Walter Zupa <zupa@fondazionecoispa.org>

task_ii2	<i>task_ii2 in GFCM DCRF datacall format</i>
----------	--

Description

task_ii2 in GFCM DCRF datacall format

Usage

task_ii2

Format

An object of class data.frame with 5 rows and 9 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

task_iii	<i>task_iii in GFCM DCRF datacall format</i>
----------	--

Description

task_iii in GFCM DCRF datacall format

Usage

task_iii

Format

An object of class data.frame with 43 rows and 16 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

task_vii2

task_vii2 in GFCM DCRF datacall format

Description

task_vii2 in GFCM DCRF datacall format

task_vii31 in GFCM DCRF datacall format

Usage

task_vii2

task_vii2

Format

An object of class data.frame with 20 rows and 13 columns.

An object of class data.frame with 20 rows and 13 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

task_vii31

task_vii31 in GFCM datacall format

Description

task_vii31 in GFCM datacall format

Usage

task_vii31

Format

An object of class data.frame with 5 rows and 8 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

`task_vii32`*task_vii32 in GFCM DCRF datacall format*

Description

`task_vii32` in GFCM DCRF datacall format

Usage

`task_vii32`

Format

An object of class `data.frame` with 10 rows and 15 columns.

Author(s)

Isabella Bitetto <bitetto@coispa.it>

Index

- * **CIRCABC**
 - circabc, 43
- * **CL**,
 - data_exampleCL, 44
- * **CS**
 - data_ex, 44
- * **DCRF**
 - task_ii2, 109
 - task_iii, 109
 - task_vii2, 110
 - task_vii32, 111
- * **DGMAREMED&BS**
 - fdi_a_catch, 46
 - fdi_g_effort, 56
 - fdi_h_spatial_land, 57
 - fdi_h_spatial_landings, 57
 - fdi_i_spatial_effort, 58
 - fdi_j_capacity, 58
- * **FDI**
 - fdi_a_catch, 46
 - fdi_g_effort, 56
 - fdi_h_spatial_land, 57
 - fdi_h_spatial_landings, 57
 - fdi_i_spatial_effort, 58
 - fdi_j_capacity, 58
- * **GFCM**
 - catfau_check, 6
 - combination_taskII2, 43
 - minmaxLtaskVII2, 97
 - minmaxLtaskVII31, 97
 - sex_mat, 107
 - task_ii2, 109
 - task_iii, 109
 - task_vii2, 110
 - task_vii31, 110
 - task_vii32, 111
- * **GSAlist**
 - GSAlist, 65
- * **Harbour**
 - circabc, 43
- * **MEDBSSP**
 - MEDBSSP, 66
- * **MED&BS**
 - ALK_tab_example, 5
 - Catch_tab_example, 5
 - Discard_tab_example, 45
 - GP_tab_example, 64
 - Landing_tab_example, 65
 - MA_tab_example, 66
 - ML_tab_example, 98
 - SA_tab_example, 107
 - SL_tab_example, 108
- * **RCG**,
 - data_exampleCL, 44
- * **RCG**
 - data_ex, 44
- * **SSPP**
 - SSPP, 108
- * **aer_catch**
 - aer_catch, 4
- * **datacall**
 - ALK_tab_example, 5
 - Catch_tab_example, 5
 - catfau_check, 6
 - combination_taskII2, 43
 - Discard_tab_example, 45
 - fdi_a_catch, 46
 - fdi_g_effort, 56
 - fdi_h_spatial_land, 57
 - fdi_h_spatial_landings, 57
 - fdi_i_spatial_effort, 58
 - fdi_j_capacity, 58
 - GP_tab_example, 64
 - Landing_tab_example, 65
 - MA_tab_example, 66
 - minmaxLtaskVII2, 97
 - minmaxLtaskVII31, 97
 - ML_tab_example, 98
 - SA_tab_example, 107
 - sex_mat, 107
 - SL_tab_example, 108
 - task_ii2, 109
 - task_iii, 109
 - task_vii2, 110
 - task_vii31, 110
 - task_vii32, 111

- * **data**
 - data_exampleCL, 44
- * **landing**
 - data_exampleCL, 44
- * **samplingData**
 - data_ex, 44
- aer_catch, 4
- ALK_tab_example, 5
- Catch_tab_example, 5
- catfau_check, 6
- check_age_MEDBS_AR, 6
- check_cs_header, 7
- check_EF_FDI_A, 8
- check_EF_FDI_G, 8
- check_EF_FDI_H, 9
- check_EF_FDI_I, 10
- check_EF_FDI_J, 10
- check_EF_taskII2, 11
- check_EF_taskIII, 12
- check_EF_taskVII2, 12
- check_EF_TaskVII31, 13
- check_EF_TaskVII32, 14
- check_gfcm_header, 14
- check_l50_TaskVII.3.1, 15
- check_ldf_TaskVII.2, 16
- check_lengths_MEDBS_AR, 16
- check_lmat_TaskVII.3.2, 17
- check_lw_TaskVII.2, 18
- check_lw_TaskVII.3.2, 19
- check_maturity_MEDBS_AR, 20
- check_minmaxl50_TaskVII.3.1, 21
- check_minmaxl_TaskVII.2, 22
- check_n_trips_MEDBS_AR, 23
- check_presence_taskII2, 23
- check_RD_FDI_A, 24
- check_RD_FDI_G, 25
- check_RD_FDI_H, 25
- check_RD_FDI_I, 26
- check_RD_FDI_J, 27
- check_RD_taskII2, 27
- check_RD_taskIII, 28
- check_RD_taskVII2, 29
- check_RD_taskVII31, 29
- check_RD_TaskVII32, 30
- check_species_catfau_TaskVII.3.2, 31
- Check_Tot_Disc, 32
- Check_Tot_Disc_gear, 33
- Check_Tot_Disc_gear_Q, 34
- Check_Tot_Disc_metier, 35
- Check_Tot_Land, 36
- Check_Tot_Land2, 37
- Check_Tot_Land3, 38
- Check_Tot_Land_gear, 39
- Check_Tot_Land_gear_Q, 40
- Check_Tot_Land_metier, 41
- check_weights_MEDBS_AR, 42
- circabc, 43
- combination_taskII2, 43
- data_ex, 44
- data_exampleCL, 44
- Discard_tab_example, 45
- fdi_a_catch, 46
- FDI_AER_land_landvalue, 45
- FDI_check_coord, 48
- FDI_checks_spatial_HI, 47
- FDI_cov_tableA, 49
- FDI_cov_tableG, 50
- FDI_cov_tableJ, 51
- FDI_coverage, 48
- FDI_cross_checks_AG, 52
- FDI_cross_checks_AH, 53
- FDI_cross_checks_IG, 54
- FDI_cross_checks_JG, 54
- FDI_disc_coverage, 55
- FDI_fishdays_cov, 56
- fdi_g_effort, 56
- fdi_h_spatial_land, 57
- fdi_h_spatial_landings, 57
- fdi_i_spatial_effort, 58
- fdi_j_capacity, 58
- FDI_landweight_cov, 59
- FDI_prices_cov, 59
- FDI_prices_not_null, 60
- FDI_vessel_lenth, 61
- FDI_vessel_numbers, 62
- GFCM_check_headers, 62
- GFCM_cov_II2, 63
- GFCM_cov_task_iii, 64
- GP_tab_example, 64
- GSAlist, 65
- Landing_tab_example, 65
- MA_tab_example, 66
- MEDBS_ALK, 67
- MEDBS_ALK_MLAA, 67
- MEDBS_ALK_NB, 68
- MEDBS_Catch_CAA, 69
- MEDBS_Catch_coverage, 70
- MEDBS_Catch_LW, 70
- MEDBS_check_disaggregated, 71

MEDBS_check_duplicates, 72
MEDBS_check_missing_years, 73
MEDBS_comp_disc_YQ, 74
MEDBS_comp_disc_YQ_fishery, 75
MEDBS_comp_land_Q_VL, 75
MEDBS_comp_land_Q_VL_fishery, 76
MEDBS_comp_land_YQ, 77
MEDBS_comp_land_YQ_fishery, 78
MEDBS_disc_mean_weight, 79
MEDBS_discard_coverage, 78
MEDBS_GP_check, 80
MEDBS_ks, 81
MEDBS_land_mean_weight, 82
MEDBS_Landing_coverage, 82
MEDBS_length_ind, 84
MEDBS_lengthclass_0, 83
MEDBS_LFD, 85
MEDBS_LW_check, 86
MEDBS_MA_check, 87
MEDBS_ML_check, 87
MEDBS_plot_disc_vol, 89
MEDBS_plot_discard_ts, 88
MEDBS_plot_land_vol, 91
MEDBS_plot_landing_ts, 90
MEDBS_SA_check, 91
MEDBS_SL_check, 92
MEDBS_SOP, 93
MEDBS_weight_0, 94
MEDBS_weight_minus1, 95
MEDBS_yr_missing_length, 96
MEDBSSP, 66
minmaxLtaskVII2, 97
minmaxLtaskVII31, 97
ML_tab_example, 98

RCG_check_AL, 98
RCG_check_CL, 99
RCG_check_LFD, 100
RCG_check_LFD_comm_cat, 101
RCG_check_loc, 101
RCG_check_lw, 102
RCG_check_mat, 103
RCG_check_mat_ogive, 104
RCG_summarize_ind_meas, 105
RCG_summarize_trips, 105
read.coded.file, 106

SA_tab_example, 107
sex_mat, 107
SL_tab_example, 108
SSPP, 108

task_ii2, 109
task_iii, 109
task_vii2, 110
task_vii31, 110
task_vii32, 111